



## STRUCTURAL STEEL IN HOUSING - THIRD EDITION



*Structural steel is playing an increasingly important role in traditional and medium density housing with its versatility, strength and competitive price.*

*OneSteel produces a unique range of steel beams, columns, channels and angles which are suitable for use in domestic housing as floor bearers, joists, roof strutting beams, lintels, piling and other applications.*

*This booklet has been compiled to assist builders, draftspersons and designers to specify and use OneSteel's range of structural steel. It contains span tables, surface treatment specifications and installation details on the use of OneSteel's structural steel products in various residential building applications.*

## **CONTENTS**

|   |           |
|---|-----------|
| <b>Benefits of Structural Steel .....</b>         | <b>1</b>  |
| <b>Product Description and Range.....</b>         | <b>2</b>  |
| <b>Span Table Design Data.....</b>                | <b>4</b>  |
| <b>Letter of Certification.....</b>               | <b>5</b>  |
| <b>Bearers .....</b>                              | <b>6</b>  |
| <b>Strutting Beams.....</b>                       | <b>8</b>  |
| <b>Strutting/Hanging Beams .....</b>              | <b>10</b> |
| <b>Lintels Supporting Roof .....</b>              | <b>12</b> |
| <b>Lintels Supporting Roof and Floor.....</b>     | <b>14</b> |
| <b>Lintels Supporting Strutting Beam .....</b>    | <b>16</b> |
| <b>Verandah Beams.....</b>                        | <b>18</b> |
| <b>Steel Sheet Roofs in High Wind Areas .....</b> | <b>20</b> |
| <b>Lintels Supporting Masonry .....</b>           | <b>22</b> |
| <b>Connection Examples .....</b>                  | <b>24</b> |
| <b>Surface Treatment.....</b>                     | <b>26</b> |
| <b>Other Publications.....</b>                    | <b>28</b> |

# Benefits of OneSteel's Structural Steels

Steel's inherent strength and consistent properties provides builders and home owners with many benefits. They include:

**Steel beam depths are around half that of timber beams offering greater usable space and lower costs of other materials**

**OneSteel's unique range of lightweight 'Lean Beam' sections in 300PLUS® grade offers efficient and cost effective design solutions**

**Superior spanning capabilities means fewer columns and more usable space**

**Steel does not warp, bow or twist due to shrinkage ensuring no long term movement problems with the steelwork**

**Unlike timber, steel does not creep and long term deflection is minimal**

**Consistent quality and dimensions ensuring ease of use and long life**



OneSteel's range of structural steel is available from hundreds of outlets Australia-wide.

Most suppliers offer cut to length and delivery services.

Many offer other services such as drilling, welding, installation and design advice.

**For an up-to-date list of suppliers please call:**

**OneSteel Direct Toll Free on 1800 1 STEEL (1800 1 78335)**

**or visit our website at [www.onesteel.com](http://www.onesteel.com)**



# PRODUCT DESCRIPTION & RANGE

OneSteel produces a large range of structural steel sections. The following sections and sizes are particularly useful for housing applications. All sections are produced in OneSteel's unique 300PLUS® steel grade offering high strength and lightweight design solutions. For information on OneSteel's full range of structural steel sections, refer to the OneSteel Product Catalogue - Structural Steel.

## PRODUCT DESCRIPTION


### UNIVERSAL BEAMS (UB)

Universal Beams are 'I' shaped members (refer diagram) designed to carry high loads over long spans. The thick flanges and thinner web efficiently proportions material to resist the high bending loads from beam applications.

A Universal Beam is designated as follows:

| 180              | UB             | 18.1             |
|------------------|----------------|------------------|
| Nominal depth, d | Universal Beam | mass/length kg/m |

The 180 UB18.1 for example is 175mm deep (d), 90mm wide (b<sub>f</sub>) with 8mm flange (t<sub>f</sub>) and 5mm web (t<sub>w</sub>).




### TAPER FLANGE BEAMS (TFB)

Taper Flange Beams are similar in shape to Universal Beams except that they have tapered flanges.

A Taper Flange Beam is designated as follows:

| 125      | TFB               |
|----------|-------------------|
| depth, d | Taper Flange Beam |

The 125 TFB for example is 125 mm deep (d), 65 mm wide (b<sub>f</sub>) with 8.5 mm flange (t<sub>f</sub>) and 5 mm web (t<sub>w</sub>).




### UNIVERSAL COLUMNS (UC)

Universal Columns are stockier, wider 'I' section members designed to carry high axial loads, for applications such as columns and piles etc. These members are generally heavier than other steel sections and are useful as supports for retaining walls and the like. They can also be used as beam sections where headroom is of concern.

A Universal Column is designated as follows:

| 150              | UC               | 37.2             |
|------------------|------------------|------------------|
| Nominal depth, d | Universal Column | mass/length kg/m |



The 150 UC 37.2 for example is 162mm deep (d), 154mm wide (b<sub>f</sub>) with 18mm flange (t<sub>f</sub>) and 8mm web (t<sub>w</sub>).

### PARALLEL FLANGE CHANNELS (PFC)

Parallel Flange Channels are a general purpose hot rolled 'C' section member useful in beam applications. PFC's provide excellent deflection resistance and strength characteristics. They are narrower than a UB of similar depth and provide a flat, flush back surface for mating with other building materials.

A Parallel Flange Channel is designated as follows:


### 180

depth, d

### PFC

Parallel Flange Channel

The 180 PFC for example, is 180mm deep (d), 75mm wide (b<sub>f</sub>) with 11mm flange (t<sub>f</sub>) and 6mm web (t<sub>w</sub>).



### UNEQUAL ANGLES (UA) AND

### EQUAL ANGLES (EA)


Angles are 'L' shaped sections and are ideal for use as lintels. One leg rests under the brickwork while the other resists the bending load over the window/door opening.

An angle is designated as follows:

| 150 x 90 x 8 | UA(or EA)  |              |                                |
|--------------|------------|--------------|--------------------------------|
| leg length   | leg length | thickness, t | Unequal Angle (or Equal Angle) |

b<sub>1</sub> b<sub>2</sub>

The 150x90x8UA for example has leg lengths of 150mm (b<sub>1</sub>) and 90mm (b<sub>2</sub>) and 8mm thickness (t).



## PRODUCT RANGE

| Section Designation             | Mass per Metre<br>kg/m | Depth of Section d<br>mm | Flange Width b <sub>f</sub><br>mm | Flange Thickness t <sub>f</sub><br>mm | Web Thickness t <sub>w</sub><br>mm |
|---------------------------------|------------------------|--------------------------|-----------------------------------|---------------------------------------|------------------------------------|
| <b>UNIVERSAL BEAMS</b>          |                        |                          |                                   |                                       |                                    |
| 150UB14.0                       | 14.0                   | 150                      | 75                                | 7.0                                   | 5.0                                |
| 150UB18.0                       | 18.0                   | 155                      | 75                                | 9.5                                   | 6.0                                |
| 180UB16.1                       | 16.1                   | 173                      | 90                                | 7.0                                   | 4.5                                |
| 180UB18.1                       | 18.1                   | 175                      | 90                                | 8.0                                   | 5.0                                |
| 180UB22.2                       | 22.2                   | 179                      | 90                                | 10.0                                  | 6.0                                |
| 200UB18.2                       | 18.2                   | 198                      | 99                                | 7.0                                   | 4.5                                |
| 200UB22.3                       | 22.3                   | 202                      | 133                               | 7.0                                   | 5.0                                |
| 200UB25.4                       | 25.4                   | 203                      | 133                               | 7.8                                   | 5.8                                |
| 200UB29.8                       | 29.8                   | 207                      | 134                               | 9.6                                   | 6.3                                |
| 250UB25.7                       | 25.7                   | 248                      | 124                               | 8.0                                   | 5.0                                |
| 250UB31.4                       | 31.4                   | 252                      | 146                               | 8.6                                   | 6.1                                |
| 250UB37.3                       | 37.3                   | 256                      | 146                               | 10.9                                  | 6.4                                |
| 310UB32.0                       | 32.0                   | 298                      | 149                               | 8.0                                   | 5.5                                |
| 310UB40.4                       | 40.4                   | 304                      | 165                               | 10.2                                  | 6.1                                |
| 310UB46.2                       | 46.2                   | 307                      | 166                               | 11.8                                  | 6.7                                |
| <b>TAPER FLANGE BEAMS</b>       |                        |                          |                                   |                                       |                                    |
| 100 TFB                         | 7.20                   | 100                      | 45                                | 6.0                                   | 4.0                                |
| 125 TFB                         | 13.1                   | 125                      | 65                                | 8.5                                   | 5.0                                |
| <b>UNIVERSAL COLUMNS</b>        |                        |                          |                                   |                                       |                                    |
| 100UC14.8                       | 14.8                   | 97                       | 99                                | 7.0                                   | 5.0                                |
| 150UC23.4                       | 23.4                   | 152                      | 152                               | 6.8                                   | 6.1                                |
| 150UC30.0                       | 30.0                   | 158                      | 153                               | 9.4                                   | 6.6                                |
| 150UC37.2                       | 37.2                   | 162                      | 154                               | 11.5                                  | 8.1                                |
| 200UC46.2                       | 46.2                   | 203                      | 203                               | 11.0                                  | 7.3                                |
| <b>PARALLEL FLANGE CHANNELS</b> |                        |                          |                                   |                                       |                                    |
| 75 PFC                          | 5.92                   | 75                       | 40                                | 6.1                                   | 3.8                                |
| 100 PFC                         | 8.33                   | 100                      | 50                                | 6.7                                   | 4.2                                |
| 125 PFC                         | 11.9                   | 125                      | 65                                | 7.5                                   | 4.7                                |
| 150 PFC                         | 17.7                   | 150                      | 75                                | 9.5                                   | 6.0                                |
| 180 PFC                         | 20.9                   | 180                      | 75                                | 11.0                                  | 6.0                                |
| 200 PFC                         | 22.9                   | 200                      | 75                                | 12.0                                  | 6.0                                |
| 230 PFC                         | 25.1                   | 230                      | 75                                | 12.0                                  | 6.5                                |
| 250 PFC                         | 35.5                   | 250                      | 90                                | 15.0                                  | 8.0                                |
| 300 PFC                         | 40.1                   | 300                      | 90                                | 16.0                                  | 8.0                                |

| Section Designation | Mass per metre<br>kg/m | Leg-Length<br>b <sub>1</sub> x b <sub>2</sub><br>mm x mm | Nominal Thickness<br>mm |
|---------------------|------------------------|--|-------------------------|
| <b>ANGLES</b>       |                        |  |                         |
| 75 x 75 x 6EA       | 6.81                   | 75 x 75  | 6                       |
| 90 x 90 x 6EA       | 8.22                   | 90 x 90  | 6                       |
| 90 x 90 x 8EA       | 10.6                   | 90 x 90  | 8                       |
| 100 x 100 x 6EA     | 9.16                   | 100 x 100  | 6                       |
| 100 x 100 x 8EA     | 11.8                   | 100 x 100  | 8                       |
| 100 x 75 x 6UA      | 7.98                   | 100 x 75   | 6                       |
| 100 x 75 x 8UA      | 10.3                   | 100 x 75   | 8                       |
| 125 x 75 x 6UA      | 9.16                   | 125 x 75   | 6                       |
| 125 x 75 x 8UA      | 11.8                   | 125 x 75   | 8                       |
| 150 x 90 x 8UA      | 14.3                   | 150 x 90   | 8                       |
| 150 x 100 x 10UA    | 18.0                   | 150 x 100  | 10                      |

All structural steel sections in this manual are designed to be 300PLUS® grade steel.



## SPAN TABLE DESIGN DATA

In compiling the span tables in this publication all requirements of the relevant standards and codes have been adopted along with established practices for Domestic Housing Structures.

In particular, the following Australian Standards have been applied:

- ◆ AS1170 Parts 1 & 2-1989 SAA Loading Code and AS4055-1992 Wind Loads for Housing.
- ◆ AS4100-1998 Steel Structures.

Other assumptions used in compiling the tables are as follows:

- ◆ All structural sections are 300PLUS® grade steel.
- ◆ Applied loads are evenly distributed along the span of the member with the exception of Strutting Beams and Lintels supporting Strutting Beams where a mid-span point load is assumed.
- ◆ Applied loads for each table are shown above the layout diagram All roof structure tables conform to wind classifications of either category N3 or N5/C2 as shown.
- ◆ Deflection limits for each table are shown above the layout diagram. Maximum deflections are for mid-span.

- ◆ All loads are static and are applied vertically.
- ◆ All members are simply supported single spans except for the continuous span floor bearer table.
- ◆ End support bearing distance for single spans is assumed to be at least that of the width of the member. For continuous spans, internal support bearing is to be at least 2 times the width of the member.
- ◆ Assumed restraint from lateral movement or buckling of the beams varies with application. The assumed conditions are given in the notes below the layout diagrams.
- ◆ The Lintels Supporting Masonry tables were compiled by BHP Research - Melbourne Laboratories before their closure in May 1998.

Applications not complying with the above conditions are outside the scope of this publication and advice should be sought from a structural engineer.

OneSteel  
Ingall Street  
MAYFIELD NSW 2304

20 September 2002

Dear Sir

### DESIGN CERTIFICATION OF STEEL SECTION SPAN TABLES

The span tables on pages 7 to 21 presented in Edition 3 of "Structural Steel in Housing" have been prepared for the loads and restraint conditions specified in the tables.

The span tables have been calculated in accordance with the principles of structural mechanics using the following standards:

- Dead and live loads in accordance with AS1170-1 1989 (Loading Code).
- Wind loads in accordance with AS1170-2 1989. The classification from AS4055 Table 1 has been adopted in referring to wind classification.
- Member sizing in accordance with AS4100-1998 (Steel Structures)

The gravity loads adopted are accepted in normal practice. The live loads are those specified by AS1170-1.

Wind loads are derived from AS1170-2. The wind pressures are suitable for domestic structures in Regions A and B (AS1170-2) for maximum gust wind speeds of 41m/s in non-cyclonic areas with wind classification up to N3 (AS4055) or 60m/s for high wind areas with wind classification up to N5 or 50m/s for cyclone areas with wind classification C2. The tables do not apply to circumstances where exceptional exposure occurs due to hilly topography or lack of shelter by other buildings.

AS4100 gives suggestions on deflection limits for beams (Appendix B) but are not mandatory. In these tables the deflection limits for bearers and lintels are span/240 or 15mm for G+0.7Q and span/360 or 10mm for 0.7Q. The deflection limits for strutting beams are span/180 or 20mm for G+0.7Q and span/240 or 15mm for 0.7Q. These values have been generally used in the industry for many years. The values originated from the Australian Domestic Construction Manual. Users of the tables should ensure that deflections are suitable for their application. Deflection criteria has not been applied to wind loads.

All members have been sized for the restraint conditions specified in the tables. Users ensure that the constructions in their application achieves that restraint.

Yours faithfully

LES MIETHKE  
Director  
McWilliam Consulting Engineers  
RPEQ Company Number 7



**McWilliam**  
CONSULTING  
ENGINEERS

#### Address

41 Fortescue Street,  
Spring Hill Qld 4000  
PO Box 304  
Spring Hill Qld 4004  
Australia

#### Telephone

+61 7 3831 3533

#### Facsimile

+61 7 3832 3835

#### Email

bris@mcwilliam.com.au

#### Visit Our Web Site

www.mcwilliam.com.au

Brisbane Office

Directors

Ken Bourke  
Gerald Croucher  
Mike Gould  
Les Miethke  
David Norris  
Brian Wooldridge

Associates

Michael Blakeney  
Greg Clowes  
Geoff Curtis  
Drew Gordon  
Peter Melloy  
Bryan Munns




QUALITY ASSURED COMPANY  
AS/NZS ISO 9002:1994  
REGION NO 128

McWilliam & Partners Pty Ltd  
ACN 009 862 702  
ABN 85 009 862 702  
Trading As  
McWilliam Consulting Engineers

# BEARERS

|   | Load (kg/m <sup>2</sup> ) |                              | Deflection Limit (mm) |                   |
|---|---------------------------|------------------------------|-----------------------|-------------------|
|   | Dead Load                 | Live Load                    | Dead & Live Load      | Live Load         |
| Bearers supporting a timber floor & non load-bearing wall | 90                        | 150<br>(or 180kg point load) | span/240<br>to 15     | span/360<br>to 10 |



**Notes:**

1. Allowance has been made in the table for a non-load bearing stud wall (not shown) within the floor area supported by the Bearer
2. The single span Bearer case is shown. For continuous Bearers over multiple spans, the variation in span between supports should not be more than 10%
3. The top flange of the bearer is assumed to be continuously laterally supported by floor joists spaced at 450mm centres

**BEARER SUPPORTING A TIMBER FLOOR AND NON LOAD BEARING STUD WALL - SINGLE SPAN**

| Section Designation | Load Width (m)                    |     |     |     |     |     |     |   |
|---------------------|-----------------------------------|-----|-----|-----|-----|-----|-----|---|
|                     | 1.2                               | 1.8 | 2.4 | 3.0 | 3.6 | 4.2 | 4.8 |   |
|                     | <b>MAXIMUM SPAN OF BEARER (m)</b> |     |     |     |     |     |     |   |
| 100TFB              | 3.0                               | 3.0 | 2.7 | 2.5 | 2.4 | 2.2 | 2.1 | <b>Example:</b><br>Refer to Fig. page 6<br>Joists continuous over bearer<br>Span of bearer=5.0m<br>A=7.6m<br>B=3.6m<br>Load width =0.6A<br>=0.6x7.6<br>=4.6m<br>Use a load width of 4.8<br>in the adjacent table:<br>a 250UB25.7 will span 5.4m<br><br>This is lighter than a 200UB29.8 |
| 125TFB              | 4.4                               | 4.1 | 3.8 | 3.6 | 3.4 | 3.2 | 3.1 |   |
| 150UB14.0           | 4.9                               | 4.5 | 4.2 | 4.0 | 3.8 | 3.7 | 3.6 |   |
| • 150UB18.0         | 5.3                               | 4.8 | 4.6 | 4.3 | 4.1 | 4.0 | 3.8 |   |
| 180UB16.1           | 5.5                               | 5.1 | 4.7 | 4.5 | 4.3 | 4.1 | 4.0 |   |
| 180UB18.1           | 5.7                               | 5.2 | 4.9 | 4.6 | 4.4 | 4.3 | 4.1 |   |
| • 180UB22.2         | 6.0                               | 5.5 | 5.2 | 4.9 | 4.7 | 4.5 | 4.4 |   |
| 200UB18.2           | 6.1                               | 5.6 | 5.2 | 5.0 | 4.7 | 4.6 | 4.4 |   |
| 200UB22.3           | 6.4                               | 5.9 | 5.6 | 5.3 | 5.1 | 4.9 | 4.7 |   |
| 200UB25.4           | 6.6                               | 6.1 | 5.7 | 5.5 | 5.2 | 5.0 | 4.9 |   |
| • 200UB29.8         | 6.9                               | 6.4 | 6.0 | 5.7 | 5.5 | 5.3 | 5.1 |   |
| 250UB25.7           | 7.3                               | 6.7 | 6.3 | 6.0 | 5.8 | 5.6 | 5.4 |   |
| 250UB31.4           | 7.6                               | 7.0 | 6.6 | 6.3 | 6.1 | 5.9 | 5.7 |   |
| • 250UB37.3         | 7.9                               | 7.4 | 7.0 | 6.7 | 6.4 | 6.2 | 6.0 |   |
| 310UB32.0           | 8.3                               | 7.7 | 7.3 | 6.9 | 6.7 | 6.4 | 6.2 |   |
| 310UB40.4           | 8.8                               | 8.2 | 7.7 | 7.4 | 7.1 | 6.9 | 6.7 |   |
| 310UB46.2           | 9.0                               | 8.4 | 8.0 | 7.6 | 7.4 | 7.1 | 6.9 |   |
| 75PFC               | 2.4                               | 2.3 | 2.1 | 1.9 | 1.8 | 1.7 | 1.7 |   |
| 100PFC              | 3.2                               | 3.1 | 2.9 | 2.7 | 2.5 | 2.4 | 2.3 |   |
| 125PFC              | 4.2                               | 4.0 | 3.7 | 3.5 | 3.3 | 3.1 | 3.0 |   |
| 150PFC              | 5.2                               | 4.8 | 4.5 | 4.2 | 4.0 | 3.9 | 3.8 |   |
| 180PFC              | 5.9                               | 5.4 | 5.1 | 4.8 | 4.6 | 4.4 | 4.3 |   |
| 200PFC              | 6.3                               | 5.8 | 5.4 | 5.2 | 5.0 | 4.8 | 4.6 |   |
| 230PFC              | 6.8                               | 6.3 | 5.9 | 5.6 | 5.4 | 5.2 | 5.0 |   |
| 250PFC              | 7.6                               | 7.0 | 6.6 | 6.3 | 6.1 | 5.9 | 5.7 |   |
| 300PFC              | 8.4                               | 7.9 | 7.4 | 7.1 | 6.8 | 6.6 | 6.4 |   |

**BEARER SUPPORTING A TIMBER FLOOR AND NON LOAD BEARING STUD WALL - CONTINUOUS SPAN**


| Section Designation | Load Width (m)                    |      |     |     |     |     |     |   |
|---------------------|-----------------------------------|------|-----|-----|-----|-----|-----|---|
|                     | 1.2                               | 1.8  | 2.4 | 3.0 | 3.6 | 4.2 | 4.8 |   |
|                     | <b>MAXIMUM SPAN OF BEARER (m)</b> |      |     |     |     |     |     |   |
| 100TFB              | 3.4                               | 3.4  | 3.1 | 2.8 | 2.5 | 2.3 | 2.2 | <b>Example:</b><br>Refer to Fig. page 6<br>Joists cantilevered<br>Span of bearer=5.0m<br>A=5.6m<br>B=3.4m<br>Load width =A <sup>2</sup> /2B<br>=5.6 <sup>2</sup> /(2x3.4)<br>=4.6m<br>Use a load width of 4.8<br>in the adjacent table:<br>a 200UB18.2 will span 5.0m<br><br>This is lighter than a 180UB22.2 |
| 125TFB              | 4.9                               | 4.7  | 4.4 | 4.2 | 3.9 | 3.6 | 3.4 |   |
| 150UB14.0           | 5.6                               | 5.2  | 4.9 | 4.6 | 4.4 | 4.0 | 3.8 |   |
| • 150UB18.0         | 6.2                               | 5.7  | 5.3 | 5.0 | 4.8 | 4.6 | 4.4 |   |
| 180UB16.1           | 6.5                               | 5.9  | 5.5 | 5.2 | 5.0 | 4.7 | 4.4 |   |
| 180UB18.1           | 6.7                               | 6.1  | 5.7 | 5.4 | 5.1 | 4.9 | 4.7 |   |
| • 180UB22.2         | 7.1                               | 6.4  | 6.0 | 5.7 | 5.4 | 5.2 | 5.1 |   |
| 200UB18.2           | 7.2                               | 6.5  | 6.1 | 5.7 | 5.5 | 5.3 | 5.0 |   |
| 200UB22.3           | 7.7                               | 7.0  | 6.5 | 6.2 | 5.9 | 5.7 | 5.5 |   |
| 200UB25.4           | 7.8                               | 7.2  | 6.7 | 6.3 | 6.1 | 5.8 | 5.6 |   |
| • 200UB29.8         | 8.2                               | 7.5  | 7.0 | 6.7 | 6.4 | 6.1 | 5.9 |   |
| 250UB25.7           | 8.7                               | 7.9  | 7.4 | 7.0 | 6.7 | 6.5 | 6.2 |   |
| 250UB31.4           | 9.0                               | 8.4  | 7.8 | 7.4 | 7.1 | 6.8 | 6.6 |   |
| • 250UB37.3         | 9.4                               | 8.8  | 8.2 | 7.8 | 7.5 | 7.2 | 7.0 |   |
| 310UB32.0           | 9.9                               | 9.1  | 8.5 | 8.1 | 7.7 | 7.5 | 7.2 |   |
| 310UB40.4           | 10.5                              | 9.7  | 9.2 | 8.7 | 8.3 | 8.0 | 7.8 |   |
| 310UB46.2           | 10.7                              | 10.0 | 9.5 | 9.0 | 8.6 | 8.3 | 8.1 |   |
| 75PFC               | 2.6                               | 2.6  | 2.5 | 2.2 | 2.0 | 1.9 | 1.7 |   |
| 100PFC              | 3.6                               | 3.6  | 3.4 | 3.0 | 2.8 | 2.6 | 2.4 |   |
| 125PFC              | 4.7                               | 4.6  | 4.3 | 4.0 | 3.7 | 3.4 | 3.2 |   |
| 150PFC              | 6.1                               | 5.5  | 5.2 | 4.9 | 4.7 | 4.5 | 4.3 |   |
| 180PFC              | 6.9                               | 6.3  | 5.9 | 5.6 | 5.3 | 5.1 | 4.9 |   |
| 200PFC              | 7.5                               | 6.8  | 6.3 | 6.0 | 5.7 | 5.5 | 5.4 |   |
| 230PFC              | 8.1                               | 7.4  | 6.9 | 6.5 | 6.3 | 6.0 | 5.8 |   |
| 250PFC              | 9.0                               | 8.4  | 7.8 | 7.4 | 7.1 | 6.8 | 6.6 |   |
| 300PFC              | 10.0                              | 9.3  | 8.8 | 8.3 | 8.0 | 7.7 | 7.5 |   |

**Notes on Tables:**

- The tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
- For sections marked '•' the next largest size may be more economical.

# STRUTTING BEAMS

|   | Load (kg/m <sup>2</sup> ) |   | Deflection Limit (mm) |                   |
|---|---------------------------|---|-----------------------|-------------------|
|   | Dead Load                 | Live Load                               | Dead & Live Load      | Live Load         |
| <b>Strutting Beam supporting a steel sheet roof &amp; ceiling</b> | 40                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/180<br>to 20     | span/240<br>to 15 |
| <b>Strutting Beam supporting a tiled roof &amp; ceiling</b>       | 90                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/180<br>to 20     | span/240<br>to 15 |



**Notes:**

1. The length of the Rafters and Ceiling Joists are assumed to be within 15% of the Strutting Beam span.
2. Both flanges of the Strutting Beam are assumed to be fully restrained at mid-span.

**STRUTTING BEAM SUPPORTING A STEEL SHEET ROOF AND CEILING - NORMAL WIND N3**

| Section<br>Designation | Load Area (m <sup>2</sup> )     |      |      |      |      |      |      |
|------------------------|---------------------------------|------|------|------|------|------|------|
|                        | 7                               | 10   | 13   | 16   | 19   | 22   | 25   |
|                        | <b>MAXIMUM SPAN OF BEAM (m)</b> |      |      |      |      |      |      |
| 100TFB                 | 3.4                             | 2.7* | 2.2* | 1.8* | 1.5* | 1.3* | 1.2* |
| 125TFB                 | 5.4                             | 5.0* | 4.7* | 4.2* | 3.6* | 3.1* | 2.8* |
| 150UB14.0              | 6.2                             | 5.7* | 5.2* | 4.6* | 4.2* | 3.9* | 3.6* |
| • 150UB18.0            |                                 | 6.3* | 5.9* | 5.6* | 5.3* | 4.9* | 4.6* |
| 180UB16.1              |                                 | 6.7* | 6.2* | 5.7* | 5.2* | 4.8* | 4.5* |
| 180UB18.1              |                                 | 6.9* | 6.5* | 6.1* | 5.8* | 5.3* | 5.0* |
| • 180UB22.2            |                                 | 7.4* | 7.0* | 6.6* | 6.2* | 6.0* | 5.8* |
| 200UB18.2              |                                 | 7.5* | 7.1* | 6.7* | 6.1* | 5.7* | 5.4* |
| 200UB22.3              |                                 |      | 7.7* | 7.3* | 6.9* | 6.6* | 6.4* |
| 200UB25.4              |                                 |      |      | 7.5* | 7.2* | 6.9* | 6.7* |
| • 200UB29.8            |                                 |      |      | 8.0* | 7.6* | 7.3* | 7.1* |
| 250UB25.7              |                                 |      |      | 8.6* | 8.2* | 7.8* | 7.6* |
| 250UB31.4              |                                 |      |      |      | 8.7* | 8.4* | 8.1* |
| • 250UB37.3            |                                 |      |      |      |      | 8.9* | 8.7* |
| 310UB32.0              |                                 |      |      |      |      | 9.4* | 9.1* |
| 310UB40.4              |                                 |      |      |      |      |      |      |
| 75PFC                  | 2.6                             | 1.8* | 1.4* | 1.1* |      |      |      |
| 100PFC                 | 4.0                             | 3.5* | 2.6* | 2.1* | 1.8* | 1.5* | 1.4* |
| 125PFC                 | 5.3                             | 4.9* | 4.5* | 3.9* | 3.3* | 2.8* | 2.5* |
| 150PFC                 |                                 | 6.1* | 5.8* | 5.4* | 5.1* | 4.9* | 4.5* |
| 180PFC                 |                                 |      | 6.8* | 6.4* | 6.1* | 5.8* | 5.6* |
| 200PFC                 |                                 |      | 7.5* | 7.1* | 6.7* | 6.4* | 6.2* |
| 230PFC                 |                                 |      |      | 7.9* | 7.5* | 7.2* | 6.9* |
| 250PFC                 |                                 |      |      |      |      | 8.4* | 8.1* |
| 300PFC                 |                                 |      |      |      |      |      |      |

**Example:**  
Refer to Fig. page 8  
Span S=6.1m  
A=7.0m  
Load area =0.25xAxS  
=0.25x7.0x6.1  
=10.7m<sup>2</sup>  
Use a load area of 13  
sq metres in the adjacent table  
a 180UB16.1 will span 6.2m  
and requires a M10 anchor rod.

**STRUTTING BEAM SUPPORTING A TILED ROOF AND CEILING - NORMAL WIND N3**

| Section<br>Designation | Load Area (m <sup>2</sup> ) |     |      |      |      |      |      |
|------------------------|-----------------------------|-----|------|------|------|------|------|
|                        | 7                           | 10  | 13   | 16   | 19   | 22   | 25   |
| 100TFB                 | 2.7                         | 2.0 | 1.6* | 1.3* | 1.1* |      |      |
| 125TFB                 | 4.6                         | 4.1 | 3.7* | 3.0* | 2.5* | 2.2* | 2.0* |
| 150UB14.0              | 5.2                         | 4.8 | 4.2* | 3.8* | 3.2* | 2.8* | 2.3* |
| • 150UB18.0            | 5.8                         | 5.2 | 4.9* | 4.6* | 4.3* | 3.7* | 3.3* |
| 180UB16.1              | 6.1                         | 5.5 | 5.1* | 4.7* | 4.3* | 3.8* | 3.4* |
| 180UB18.1              | 6.4                         | 5.8 | 5.4* | 5.0* | 4.7* | 4.3* | 3.8* |
| • 180UB22.2            | 6.8                         | 6.2 | 5.8* | 5.4* | 5.1* | 4.9* | 4.7* |
| 200UB18.2              | 6.9                         | 6.3 | 5.9* | 5.5* | 5.0* | 4.7* | 4.4* |
| 200UB22.3              |                             | 6.9 | 6.4* | 6.0* | 5.7* | 5.4* | 5.3* |
| 200UB25.4              |                             | 7.1 | 6.6* | 6.2* | 5.9* | 5.6* | 5.5* |
| • 200UB29.8            |                             | 7.6 | 7.1* | 6.7* | 6.3* | 6.0* | 5.8* |
| 250UB25.7              |                             | 8.1 | 7.6* | 7.1* | 6.8* | 6.5* | 6.2* |
| 250UB31.4              |                             |     | 8.1* | 7.7* | 7.3* | 6.9* | 6.7* |
| • 250UB37.3            |                             |     |      | 8.2* | 7.8* | 7.4* | 7.2* |
| 310UB32.0              |                             |     |      | 8.6* | 8.1* | 7.8* | 7.5* |
| 310UB40.4              |                             |     |      |      | 9.0* | 8.6* | 8.3* |
| 310UB46.2              |                             |     |      |      |      | 9.0* | 8.7* |
| 75PFC                  | 1.8                         | 1.3 | 1.0* |      |      |      |      |
| 100PFC                 | 3.3                         | 2.4 | 1.8* | 1.5* | 1.3* | 1.1* |      |
| 125PFC                 | 4.4                         | 4.0 | 3.4* | 2.7* | 2.3* | 2.0* | 1.8* |
| 150PFC                 | 5.6                         | 5.1 | 4.7* | 4.4* | 4.1* | 3.5* | 3.1* |
| 180PFC                 | 6.6                         | 6.1 | 5.6* | 5.3* | 5.0* | 4.6* | 4.1* |
| 200PFC                 |                             | 6.7 | 6.2* | 5.8* | 5.5* | 5.3* | 5.0* |
| 230PFC                 |                             | 7.4 | 6.9* | 6.5* | 6.2* | 5.9* | 5.7* |
| 250PFC                 |                             |     |      | 7.7* | 7.3* | 7.0* | 6.7* |
| 300PFC                 |                             |     |      |      | 8.5* | 8.1* | 7.8* |


**Example:**  
Refer to Fig. page 8  
Span S=6.1m  
A=7.0m  
Load area=0.25xAxS  
=0.25x7.0x6.1  
=10.7m<sup>2</sup>  
Use load area of 13  
sq metres in the adjacent table  
a 200UB22.3 will span 6.4m  
and requires a M10 anchor rod.

**Notes on Tables:**

- The tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
- For sections marked '•' the next largest size may be more economical.
- No symbol next to the span indicates that only nominal holding down is required (uplift is less than 5 kN).  
A "\*" indicates a M10 holding down rod is required (uplift is between 5 and 19 kN).
- For a steel sheet roof in high wind load areas refer to the table on page 20.

# STRUTTING/HANGING BEAMS

|  | Load (kg/m <sup>2</sup> ) |   | Deflection Limit (mm) |                   |
|--|---------------------------|---|-----------------------|-------------------|
|  | Dead Load                 | Live Load                               | Dead & Live Load      | Live Load         |
| Strutting/Hanging Beam supporting a steel sheet roof & ceiling | 40                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/180<br>to 20     | span/240<br>to 15 |
| Strutting/Hanging Beam supporting a tiled roof & ceiling       | 90                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/180<br>to 20     | span/240<br>to 15 |



**Notes:**

1. The roof load is assumed to be evenly distributed along the Strutting/Hanging Beam.
2. The bottom flange of the Strutting/Hanging Beam is assumed to be continuously laterally supported by ceiling joists at 600mm maximum centres.

**STRUTTING/HANGING BEAM SUPPORTING A STEEL SHEET ROOF AND CEILING - NORMAL WIND N3**

| Section<br>Designation | Load Width (m)                  |      |      |      |      |      |      |
|------------------------|---------------------------------|------|------|------|------|------|------|
|                        | 1.2                             | 1.8  | 2.4  | 3.0  | 3.6  | 4.2  | 4.8  |
|                        | <b>MAXIMUM SPAN OF BEAM (m)</b> |      |      |      |      |      |      |
| 100TFB                 | 3.1                             | 2.8  | 2.6  | 2.4  | 2.2* | 2.1* | 2.0* |
| 125TFB                 | 5.0                             | 4.4* | 4.0* | 3.7* | 3.5* | 3.3* | 3.2* |
| 150UB14.0              | 5.0                             | 4.5* | 4.1* | 3.8* | 3.6* | 3.4* | 3.2* |
| • 150UB18.0            | 6.0                             | 5.3* | 4.8* | 4.5* | 4.2* | 4.0* | 3.8* |
| 180UB16.1              | 5.6                             | 5.0* | 4.6* | 4.2* | 4.0* | 3.8* | 3.7* |
| 180UB18.1              |                                 | 5.4* | 4.9* | 4.6* | 4.3* | 4.1* | 3.9* |
| • 180UB22.2            |                                 | 6.1* | 5.6* | 5.2* | 4.9* | 4.7* | 4.5* |
| 200UB18.2              |                                 | 5.4* | 5.0* | 4.6* | 4.4* | 4.2* | 4.0* |
| 200UB22.3              |                                 | 6.4* | 5.9* | 5.5* | 5.2* | 5.0* | 4.8* |
| 200UB25.4              |                                 | 6.9* | 6.3* | 5.9* | 5.6* | 5.3* | 5.1* |
| • 200UB29.8            |                                 | 7.7* | 7.0* | 6.6* | 6.2* | 5.9* | 5.7* |
| 250UB25.7              |                                 | 6.8* | 6.2* | 5.8* | 5.5* | 5.3* | 5.0* |
| 250UB31.4              |                                 |      | 7.1* | 6.7* | 6.3* | 6.0* | 5.8* |
| • 250UB37.3            |                                 |      | 8.0* | 7.5* | 7.4* | 6.8* | 6.5+ |
| 310UB32.0              |                                 |      | 7.1* | 6.7* | 6.4* | 6.1* | 5.8* |
| 310UB40.4              |                                 |      |      | 8.0* | 7.5* | 7.2+ | 6.9+ |
| 310UB46.2              |                                 |      |      |      | 8.2* | 7.8+ | 7.5+ |
| 75PFC                  | 3.1                             | 2.8  | 2.5  | 2.3  | 2.2* | 2.1* | 2.0* |
| 100PFC                 | 4.0                             | 3.5  | 3.2* | 2.9* | 2.8* | 2.6* | 2.5* |
| 125PFC                 | 5.1                             | 4.5* | 4.1* | 3.8* | 3.6* | 3.4* | 3.2* |
| 150PFC                 |                                 | 5.7* | 5.2* | 4.9* | 4.6* | 4.4* | 4.2* |
| 180PFC                 |                                 | 6.3* | 5.7* | 5.3* | 5.0* | 4.8* | 4.6* |
| 200PFC                 |                                 | 6.6* | 6.1* | 5.6* | 5.3* | 5.1* | 4.8* |
| 230PFC                 |                                 | 6.8* | 6.2* | 5.8* | 5.5* | 5.2* | 5.0* |
| 250PFC                 |                                 |      |      | 7.4* | 7.0* | 6.6* | 6.3+ |
| 300PFC                 |                                 |      |      | 7.7* | 7.3* | 7.0* | 6.7+ |

**Example:**  
Refer to Fig. page 10  
Required beam span=4.0m  
A=7.8m, B=6.0m  
Load width= Maximum of  
=0.5A & 0.5B  
=0.5x7.8  
= 3.9m  
Use a load width of 4.2  
in the adjacent table  
a 150UB18.0 will span 4.0m  
and requires a M10 anchor rod.

**STRUTTING/HANGING BEAM SUPPORTING A TILED ROOF AND CEILING - NORMAL WIND N3**

| Section<br>Designation | Load Width (m)                  |      |      |      |      |      |      |
|------------------------|---------------------------------|------|------|------|------|------|------|
|                        | 1.2                             | 1.8  | 2.4  | 3.0  | 3.6  | 4.2  | 4.8  |
|                        | <b>MAXIMUM SPAN OF BEAM (m)</b> |      |      |      |      |      |      |
| 100TFB                 | 2.7                             | 2.4  | 2.2  | 2.1  | 1.9  | 1.8  | 1.7  |
| 125TFB                 | 4.4                             | 3.8  | 3.5  | 3.2  | 3.0* | 2.9* | 2.7* |
| 150UB14.0              | 4.5                             | 3.9  | 3.6  | 3.3  | 3.1* | 3.0* | 2.8* |
| • 150UB18.0            | 5.3                             | 4.6  | 4.2  | 3.9* | 3.7* | 3.5* | 3.3* |
| 180UB16.1              | 5.0                             | 4.4  | 4.0  | 3.7* | 3.5* | 3.3* | 3.2* |
| 180UB18.1              | 5.4                             | 4.7  | 4.3  | 4.0* | 3.8* | 3.6* | 3.4* |
| • 180UB22.2            | 6.1                             | 5.4  | 4.9* | 4.6* | 4.3* | 4.1* | 3.9* |
| 200UB18.2              | 5.4                             | 4.8  | 4.4  | 4.1* | 3.8* | 3.7* | 3.5* |
| 200UB22.3              | 6.4                             | 5.7  | 5.2* | 4.9* | 4.6* | 4.4* | 4.2* |
| 200UB25.4              | 6.9                             | 6.1  | 5.6* | 5.2* | 4.9* | 4.7* | 4.5* |
| • 200UB29.8            | 7.7                             | 6.8  | 6.2* | 5.8* | 5.5* | 5.2* | 5.0* |
| 250UB25.7              | 6.8                             | 6.0  | 5.5* | 5.1* | 4.9* | 4.6* | 4.4* |
| 250UB31.4              |                                 | 6.9  | 6.3* | 5.9* | 5.6* | 5.3* | 5.1* |
| • 250UB37.3            |                                 | 7.7* | 7.1* | 6.6* | 6.3* | 6.0* | 5.7* |
| 310UB32.0              |                                 | 6.9  | 6.4* | 5.9* | 5.6* | 5.4* | 5.2* |
| 310UB40.4              |                                 |      | 7.5* | 7.1* | 6.7* | 6.4* | 6.1* |
| 310UB46.2              |                                 |      | 8.2* | 7.6* | 7.2* | 6.9* | 6.6* |
| 75PFC                  | 2.7                             | 2.4  | 2.2  | 2.0  | 1.9  | 1.8  | 1.7  |
| 100PFC                 | 3.5                             | 3.0  | 2.8  | 2.5  | 2.4  | 2.3  | 2.2  |
| 125PFC                 | 4.5                             | 3.9  | 3.6  | 3.3  | 3.1* | 2.9* | 2.8* |
| 150PFC                 | 5.7                             | 5.0  | 4.6  | 4.3* | 4.0* | 3.8* | 3.6* |
| 180PFC                 | 6.3                             | 5.5  | 5.0* | 4.7* | 4.4* | 4.2* | 4.0* |
| 200PFC                 | 6.6                             | 5.8  | 5.3* | 4.9* | 4.6* | 4.4* | 4.2* |
| 230PFC                 | 6.8                             | 6.0  | 5.5* | 5.1* | 4.8* | 4.6* | 4.4* |
| 250PFC                 |                                 | 7.6* | 7.0* | 6.5* | 6.1* | 5.8* | 5.6* |
| 300PFC                 |                                 |      | 7.3* | 6.8* | 6.5* | 6.1* | 5.9* |


**Example:**  
Refer to Fig. page 10  
Required beam span=4.5m  
A=7.6m  
B=7.4m  
Load width=0.5A  
=0.5x7.6  
=3.8m  
Use a load width of 4.2  
in the adjacent table  
a 200UB25.4 will span 4.7m  
and requires a M10 anchor rod.

**Notes on Tables:**

- The tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
- For sections marked '•' the next largest size may be more economical.
- No symbol next to the span indicates that only nominal holding down is required (uplift is less than 5 kN). A "\*" indicates a M10 holding down rod is required (uplift is between 5 and 19 kN). A "+" indicates a M12 holding down bolt is required (uplift is between 19 & 27 kN).
- For a steel sheet roof in high wind load areas refer to the table on page 20.


# LINTELS SUPPORTING ROOF

|   | Load (kg/m <sup>2</sup> ) |   | Deflection Limit (mm) |                   |
|---|---------------------------|---|-----------------------|-------------------|
|   | Dead Load                 | Live Load                               | Dead & Live Load      | Live Load         |
| <b>Lintel supporting a steel sheet roof &amp; ceiling</b> | 40                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/240<br>to 15     | span/360<br>to 10 |
| <b>Lintel supporting tiled roof &amp; ceiling</b>         | 90                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/240<br>to 15     | span/360<br>to 10 |



**Notes:**

1. Attention should be given to the load carrying capacity of the timber studs or steel columns that support the Lintel.
2. The top flange of Lintel is assumed to be continuously laterally supported by trusses spaced at 900mm maximum centres. Angles must also be prevented from twisting.



**Notes:**

1. If A is much greater than C or vice versa, then the Lintel selection from the table will be conservative.
2. Attention should be given to the load carrying capacity of the timber studs or steel columns that support the Lintel.
3. The top flange of the Lintel is assumed to be continuously laterally supported by joists and rafters spaced at 900mm maximum centres. Angles must also be prevented from twisting.

**LINTEL SUPPORTING A STEEL SHEET ROOF AND CEILING - NORMAL WIND N3**

| Section Designation | Load Width (m)                    |      |      |      |      |      |      |
|---------------------|-----------------------------------|------|------|------|------|------|------|
|                     | 1.2                               | 1.8  | 2.4  | 3.0  | 3.6  | 4.8  |      |
|                     | <b>MAXIMUM SPAN OF LINTEL (m)</b> |      |      |      |      |      |      |
| 100TFB              | 3.7                               | 3.2  | 2.9  | 2.7* | 2.5* | 2.3* | 2.1* |
| 125TFB              | 5.7                               | 5.1* | 4.6* | 4.2* | 4.0* | 3.6* | 3.3* |
| 150UB14.0           | 6.1                               | 5.2* | 4.7* | 4.4* | 4.1* | 3.7* | 3.4* |
| • 150UB18.0         | 6.8                               | 6.2  | 5.6* | 5.2* | 4.9* | 4.4* | 4.0* |
| 180UB16.1           | 6.8*                              | 5.9* | 5.4* | 5.0* | 4.7* | 4.2* | 3.9* |
| 180UB18.1           |                                   | 6.4* | 5.8* | 5.3* | 5.0* | 4.5* | 4.2* |
| • 180UB22.2         |                                   | 7.2* | 6.6* | 6.1* | 5.7* | 5.1* | 4.7* |
| 200UB18.2           |                                   | 6.5* | 5.9* | 5.4* | 5.1* | 4.6* | 4.3* |
| 200UB22.3           |                                   | 7.8* | 7.1* | 6.5* | 6.1* | 5.6* | 5.2+ |
| 200UB25.4           |                                   | 8.0* | 7.5* | 7.0* | 6.5* | 5.9* | 5.5+ |
| • 200UB29.8         |                                   | 8.4* | 7.9* | 7.5* | 7.2* | 6.6+ | 6.1+ |
| 250UB25.7           |                                   | 8.3* | 7.5* | 6.9* | 6.5* | 5.9* | 5.5+ |
| 250UB31.4           |                                   |      | 8.7* | 8.0* | 7.5* | 6.8+ | 6.3+ |
| 250UB37.3           |                                   |      | 9.2* | 8.8* | 8.5+ | 7.7+ |      |
| 75PFC               | 3.5                               | 3.1  | 2.8  | 2.6* | 2.4* | 2.2* | 2.0* |
| 100PFC              | 4.5                               | 4.0  | 3.6* | 3.3* | 3.1* | 2.8* | 2.5* |
| 125PFC              | 5.6                               | 5.2* | 4.7* | 4.3* | 4.0* | 3.6* | 3.3* |
| 150PFC              |                                   | 6.2* | 5.9* | 5.6* | 5.2* | 4.7* | 4.3* |
| 180PFC              |                                   | 7.1* | 6.7* | 6.2* | 5.8* | 5.2* | 4.8+ |
| 200PFC              |                                   | 7.6* | 7.1* | 6.6* | 6.2* | 5.5* | 5.1+ |
| 230PFC              |                                   | 8.2* | 7.4* | 6.8* | 6.4* | 5.8* | 5.3+ |
| 250PFC              |                                   |      |      | 8.4* | 8.0* | 7.4+ | 6.8+ |
| 75 x 75 x 5EA       | 2.8                               | 2.5  | 2.3  | 2.1  | 1.9  | 1.6  |      |
| 90 x 90 x 6EA       | 3.7                               | 3.4  | 3.2  | 2.9* | 2.6* | 2.3* |      |
| 100 x 75 x 6UA      | 3.9                               | 3.7  | 3.4* | 3.0* | 2.7* | 2.4* |      |
| 100 x 100 x 6EA     | 4.0                               | 3.8  | 3.5* | 3.2* | 2.9* | 2.5* |      |
| 125 x 75 x 6UA      | 4.6                               | 4.3* | 4.0* | 3.1* | 3.2* | 2.8* |      |
| 150 x 90 x 8UA      | 5.7                               | 5.3* | 5.0* | 3.6* | 4.6* | 3.9* |      |
| 150 x 100 x 10UA    | 6.0                               | 5.6* | 5.3* | 5.0* | 4.9* | 4.5* |      |

**Example:**  
Refer to Fig. page 12  
Lintel Span=4.6m, trussed roof  
A=4.7m  
Load width=A  
=4.7m  
Use a load width of 4.8 in  
the adjacent table a 200UB18.2  
will span 4.6m and requires a  
M10 anchor rod.

**LINTEL SUPPORTING A TILED ROOF AND CEILING - NORMAL WIND N3**

| Section Designation | Load Width (m)                    |      |      |      |      |      |      |
|---------------------|-----------------------------------|------|------|------|------|------|------|
|                     | 1.2                               | 1.8  | 2.4  | 3.0  | 3.6  | 4.8  |      |
|                     | <b>MAXIMUM SPAN OF LINTEL (m)</b> |      |      |      |      |      |      |
| 100TFB              | 3.8                               | 3.4  | 3.2  | 3.0  | 2.8  | 2.4* | 2.2* |
| 125TFB              | 5.0                               | 4.6  | 4.3  | 4.1* | 3.9* | 3.7* | 3.4* |
| 150UB14.0           | 5.6                               | 5.1  | 4.8* | 4.6* | 4.4* | 4.1* | 3.9* |
| • 150UB18.0         | 6.0                               | 5.5  | 5.2* | 4.9* | 4.7* | 4.4* | 4.2* |
| 180UB16.1           | 6.3                               | 5.8  | 5.4* | 5.1* | 4.9* | 4.6* | 4.3* |
| 180UB18.1           | 6.5                               | 5.9  | 5.6* | 5.3* | 5.1* | 4.7* | 4.5* |
| • 180UB22.2         | 6.8                               | 6.3  | 5.9* | 5.6* | 5.4* | 5.0* | 4.7* |
| 200UB18.2           | 6.9                               | 6.4  | 6.0* | 5.7* | 5.4* | 5.1* | 4.8* |
| 200UB22.3           | 7.4                               | 6.8* | 6.4* | 6.1* | 5.8* | 5.4* | 5.1* |
| 200UB25.4           | 7.6                               | 7.0* | 6.6* | 6.2* | 6.0* | 5.6* | 5.3* |
| • 200UB29.8         | 8.0                               | 7.4* | 6.9* | 6.6* | 6.3* | 5.9* | 5.6* |
| 250UB25.7           | 8.4                               | 7.8* | 7.3* | 6.9* | 6.6* | 6.2* | 5.9* |
| 250UB31.4           |                                   | 8.2* | 7.7* | 7.3* | 7.0* | 6.5* | 6.2* |
| 250UB37.3           |                                   | 8.6* | 8.1* | 7.7* | 7.4* | 6.9* | 6.5* |
| 75PFC               | 2.9                               | 2.6  | 2.4  | 2.3  | 2.1  | 2.0  | 1.8* |
| 100PFC              | 3.9                               | 3.6  | 3.4  | 3.1  | 3.0  | 2.7* | 2.5* |
| 125PFC              | 4.9                               | 4.5  | 4.2  | 4.0* | 3.8* | 3.6* | 3.3* |
| 150PFC              | 5.9                               | 5.4  | 5.1* | 4.8* | 4.6* | 4.3* | 4.1* |
| 180PFC              | 6.7                               | 6.2  | 5.8* | 5.5* | 5.3* | 4.9* | 4.7* |
| 200PFC              | 7.2                               | 6.6* | 6.2* | 5.9* | 5.7* | 5.3* | 5.0* |
| 230PFC              | 7.8                               | 7.2* | 6.8* | 6.4* | 6.2* | 5.8* | 5.5* |
| 250PFC              |                                   | 8.2* | 7.7* | 7.3* | 7.0* | 6.5* | 6.2* |
| 75 x 75 x 5EA       | 2.3                               | 2.1  | 1.9  | 1.7  | 1.6  | 1.4  |      |
| 90 x 90 x 6EA       | 3.1                               | 2.8  | 2.6  | 2.4  | 2.2  | 1.9  |      |
| 100 x 75 x 6UA      | 3.4                               | 3.1  | 2.8  | 2.5  | 2.3  | 2.0  |      |
| 100 x 100 x 6EA     | 3.5                               | 3.2  | 2.9  | 2.7  | 2.4  | 2.1  |      |
| 125 x 75 x 6UA      | 4.1                               | 3.8  | 3.5  | 3.2  | 2.8  | 2.5* |      |
| 150 x 90 x 8UA      | 5.0                               | 4.6  | 4.3  | 4.1* | 4.0* | 3.5* |      |
| 150 x 100 x 10UA    | 5.3                               | 4.8  | 4.6  | 4.3* | 4.2* | 3.9* |      |


**Example:**  
Refer to Fig. page 12  
Lintel Span=4.6m,  
conventional roof  
A=3.9m  
B=3.0m, C=4.5m  
Load width=A<sup>2</sup>/(2B)  
=3.9<sup>2</sup>/(2x3.0)  
=2.5m  
Use a load width of 3.0  
in the adjacent table a 150UB14.0  
will span 4.6m and requires a  
M10 anchor rod.

**Notes on Tables:**

- The tables apply for 300PLUS<sup>®</sup> steel only. For details of your nearest 300PLUS<sup>®</sup> structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website [www.onesteel.com](http://www.onesteel.com)
- For angle lintels, the first dimension corresponds to the vertical lintel leg, eg for 100x75x6UA, 100mm leg is vertical.
- For sections marked '•' the next largest size may be more economical.
- No symbol next to the span indicates that only nominal holding down is required (uplift is less than 5 kN).  
A "\*" indicates a M10 holding down rod is required (uplift is between 5 and 19 kN).  
A "+" indicates a M12 holding down bolt is required (uplift is between 19 and 27 kN).
- For a steel sheet roof in high wind load areas refer to the table on page 21.


# LINTELS SUPPORTING ROOF AND FLOOR

|  | Load (kg/m <sup>2</sup> ) |           | Deflection Limit (mm) |                |
|--|---------------------------|-----------|-----------------------|----------------|
|  | Dead Load                 | Live Load | Dead & Live Load      | Live Load      |
| Lintel supporting timber floor, steel sheet roof & ceiling | 130                       | 175       | span/240 to 15        | span/360 to 10 |
| Lintel supporting timber floor, tiled roof & ceiling       | 130                       | 175       | span/240 to 15        | span/360 to 10 |



**Notes:**

1. If A is much greater than C or vice versa, then the Lintel selection from the table will be conservative.
2. If there is no cantilevered floor then set C=D in the calculation of Load Width.
3. Attention should be given to the load carrying capacity of the timber studs or steel columns that support the Lintel.
4. The top flange of the Lintel is assumed to be continuously laterally supported by floor joists spaced at 450mm centres.



**Notes:**

1. If A<sup>2</sup>/2B is much greater than C<sup>2</sup>/2D or vice versa, then the Lintel selection from the table will be conservative.
2. E is to be no more than 10% greater than A.
3. If there is no cantilevered floor then set C=D in the calculation of Load Width.
4. Attention should be given to the load carrying capacity of the timber studs or steel columns that support the Lintel.
5. The top flange of the Lintel is assumed to be continuously laterally supported by Floor Joists spaced at 450mm centres.

**LINTEL SUPPORTING A TIMBER FLOOR, STEEL SHEET ROOF AND CEILING - NORMAL WIND N3**

| Section Designation | Load Width (m)                    |     |     |     |     |      |      |
|---------------------|-----------------------------------|-----|-----|-----|-----|------|------|
|                     | 1.2                               | 1.8 | 2.4 | 3.0 | 3.6 | 4.2  | 4.8  |
|                     | <b>MAXIMUM SPAN OF LINTEL (m)</b> |     |     |     |     |      |      |
| 100TFB              | 2.9                               | 2.6 | 2.4 | 2.2 | 2.0 | 1.9  | 1.8  |
| 125TFB              | 4.0                               | 3.7 | 3.4 | 3.2 | 3.0 | 2.9  | 2.7  |
| 150UB14.0           | 4.4                               | 4.1 | 3.8 | 3.6 | 3.5 | 3.3  | 3.2  |
| • 150UB18.0         | 4.8                               | 4.4 | 4.1 | 3.9 | 3.8 | 3.6  | 3.5  |
| 180UB16.1           | 5.0                               | 4.6 | 4.3 | 4.1 | 3.9 | 3.8  | 3.7  |
| 180UB18.1           | 5.2                               | 4.7 | 4.4 | 4.2 | 4.0 | 3.9  | 3.8  |
| • 180UB22.2         | 5.5                               | 5.0 | 4.7 | 4.5 | 4.3 | 4.1  | 4.0  |
| 200UB18.2           | 5.5                               | 5.1 | 4.8 | 4.5 | 4.3 | 4.2  | 4.0  |
| 200UB22.3           | 5.9                               | 5.4 | 5.1 | 4.8 | 4.7 | 4.5  | 4.3  |
| 200UB25.4           | 6.1                               | 5.6 | 5.2 | 5.0 | 4.8 | 4.6  | 4.5* |
| • 200UB29.8         | 6.4                               | 5.9 | 5.5 | 5.3 | 5.0 | 4.9  | 4.7* |
| 250UB25.7           | 6.7                               | 6.2 | 5.8 | 5.5 | 5.3 | 5.1  | 5.0* |
| 250UB31.4           | 7.1                               | 6.5 | 6.1 | 5.8 | 5.6 | 5.4* | 5.2* |
| 250UB37.3           | 7.5                               | 6.9 | 6.5 | 6.2 | 5.9 | 5.7* | 5.5* |
| 310UB32.0           | 7.7                               | 7.1 | 6.7 | 6.4 | 6.1 | 5.9* | 5.7* |
| 310UB40.4           | 8.3                               | 7.7 | 7.2 | 6.9 | 6.6 | 6.4* | 6.2* |
| 310UB46.2           | 8.6                               | 8.0 | 7.5 | 7.1 | 6.9 | 6.6* | 6.4* |
| 75PFC               | 2.2                               | 2.0 | 1.8 | 1.7 | 1.6 | 1.5  | 1.4  |
| 100PFC              | 3.1                               | 2.7 | 2.5 | 2.3 | 2.2 | 2.1  | 2.0  |
| 125PFC              | 3.9                               | 3.6 | 3.3 | 3.1 | 2.9 | 2.8  | 2.7  |
| 150PFC              | 4.7                               | 4.3 | 4.0 | 3.8 | 3.7 | 3.6  | 3.4  |
| 180PFC              | 5.3                               | 4.9 | 4.6 | 4.4 | 4.2 | 4.1  | 3.9  |
| 200PFC              | 5.8                               | 5.3 | 5.0 | 4.7 | 4.5 | 4.4  | 4.2  |
| 230PFC              | 6.3                               | 5.8 | 5.4 | 5.2 | 4.9 | 4.8  | 4.6* |
| 250PFC              | 7.1                               | 6.5 | 6.2 | 5.9 | 5.6 | 5.4  | 5.3* |
| 300PFC              | 8.0                               | 7.4 | 6.9 | 6.6 | 6.3 | 6.1* | 5.9* |

**Example:**  
Refer to Fig. page 14  
Lintel Span=4.6m, trussed roof  
A=3.8m  
C=3.0m D=1.5m  
Load width is the max of  
=A or C<sup>2</sup>/2D  
=3.8 or 3.0<sup>2</sup>/(2x1.5)  
=3.8m  
Use a load width of 4.2  
in the adjacent table  
a 200UB25.4 will span 4.6m.  
No anchor rod is required.

**LINTEL SUPPORTING A TIMBER FLOOR, TILED ROOF AND CEILING - NORMAL WIND N3**

| Section Designation | Load Width (m)                    |     |     |     |     |     |     |
|---------------------|-----------------------------------|-----|-----|-----|-----|-----|-----|
|                     | 1.2                               | 1.8 | 2.4 | 3.0 | 3.6 | 4.2 | 4.8 |
|                     | <b>MAXIMUM SPAN OF LINTEL (m)</b> |     |     |     |     |     |     |
| 100TFB              | 2.7                               | 2.4 | 2.2 | 2.1 | 1.9 | 1.8 | 1.7 |
| 125TFB              | 3.8                               | 3.5 | 3.2 | 3.0 | 2.8 | 2.7 | 2.6 |
| 150UB14.0           | 4.3                               | 3.9 | 3.7 | 3.5 | 3.3 | 3.1 | 3.0 |
| • 150UB18.0         | 4.6                               | 4.2 | 4.0 | 3.8 | 3.6 | 3.5 | 3.3 |
| 180UB16.1           | 4.8                               | 4.4 | 4.1 | 3.9 | 3.8 | 3.6 | 3.5 |
| 180UB18.1           | 5.0                               | 4.6 | 4.3 | 4.1 | 3.9 | 3.7 | 3.6 |
| • 180UB22.2         | 5.3                               | 4.8 | 4.5 | 4.3 | 4.1 | 4.0 | 3.8 |
| 200UB18.2           | 5.3                               | 4.9 | 4.6 | 4.3 | 4.2 | 4.0 | 3.9 |
| 200UB22.3           | 5.7                               | 5.2 | 4.9 | 4.7 | 4.5 | 4.3 | 4.2 |
| 200UB25.4           | 5.9                               | 5.4 | 5.0 | 4.8 | 4.6 | 4.4 | 4.3 |
| • 200UB29.8         | 6.2                               | 5.7 | 5.3 | 5.0 | 4.8 | 4.7 | 4.5 |
| 250UB25.7           | 6.5                               | 5.9 | 5.6 | 5.3 | 5.1 | 4.9 | 4.7 |
| 250UB31.4           | 6.8                               | 6.3 | 5.9 | 5.6 | 5.4 | 5.2 | 5.0 |
| 250UB37.3           | 7.2                               | 6.6 | 6.2 | 5.9 | 5.7 | 5.5 | 5.3 |
| 310UB32.0           | 7.5                               | 6.9 | 6.4 | 6.1 | 5.9 | 5.7 | 5.5 |
| 310UB40.4           | 8.0                               | 7.4 | 7.0 | 6.6 | 6.3 | 6.1 | 5.9 |
| 310UB46.2           | 8.3                               | 7.7 | 7.2 | 6.9 | 6.6 | 6.3 | 6.2 |
| 75PFC               | 2.1                               | 1.9 | 1.7 | 1.6 | 1.5 | 1.4 | 1.3 |
| 100PFC              | 2.9                               | 2.6 | 2.4 | 2.2 | 2.1 | 2.0 | 1.9 |
| 125PFC              | 3.8                               | 3.4 | 3.1 | 2.9 | 2.7 | 2.6 | 2.5 |
| 150PFC              | 4.5                               | 4.1 | 3.9 | 3.7 | 3.5 | 3.4 | 3.2 |
| 180PFC              | 5.2                               | 4.7 | 4.4 | 4.2 | 4.0 | 3.9 | 3.8 |
| 200PFC              | 5.6                               | 5.1 | 4.8 | 4.5 | 4.4 | 4.2 | 4.1 |
| 230PFC              | 6.0                               | 5.5 | 5.2 | 4.9 | 4.7 | 4.6 | 4.4 |
| 250PFC              | 6.9                               | 6.3 | 5.9 | 5.6 | 5.4 | 5.2 | 5.0 |
| 300PFC              | 7.7                               | 7.1 | 6.7 | 6.3 | 6.1 | 5.9 | 5.7 |


**Example:**  
Refer to Fig. page 14  
Lintel Span=4.6m, trussed roof  
A=3.8m  
C=3.0m D=1.0m  
Load width is the max of  
=A or (C<sup>2</sup>/2D)  
=3.8 or 3<sup>2</sup>/(2x1.0)  
=4.5m  
Use a load width of 4.8  
in the adjacent table  
a 200UB25.7 will span 4.7m.  
No anchor rod is required.

**Notes on Tables:**

- The tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
- For angle lintels, the first dimension corresponds to the vertical lintel leg, eg for 100x75x6UA, 100mm leg is vertical.
- For sections marked '•' the next largest size may be more economical.
- No symbol next to the span indicates that only nominal holding down is required (uplift is less than 5 kN).  
A "\*" indicates a M10 holding down rod is required (uplift is between 5 and 19 kN).

# LINTELS SUPPORTING STRUTTING BEAM (or Girder Truss)

|  | Load (kg/m <sup>2</sup> ) |   | Deflection Limit (mm) |                   |
|--|---------------------------|---|-----------------------|-------------------|
|  | Dead Load                 | Live Load                               | Dead & Live Load      | Live Load         |
| Lintel supporting strutting beam, steel sheet roof and ceiling | 40                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/240<br>to 15     | span/360<br>to 10 |
| Lintel supporting strutting beam, tiled roof and ceiling       | 90                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/240<br>to 15     | span/360<br>to 10 |



**Notes:**

1. The length of the rafters are assumed to be within 15% of the Strutting Beam span (B).
2. The Strutting Beam is assumed to be supported by the Lintel at mid-span.
3. The top flange of the Lintel is assumed to be laterally supported at mid-span.

**LINTEL SUPPORTING A STRUTTING BEAM, STEEL SHEET ROOF AND CEILING - NORMAL WIND N3**

| Section<br>Designation | Load Area (m <sup>2</sup> )       |      |      |      |      |      |      |
|------------------------|-----------------------------------|------|------|------|------|------|------|
|                        | 7                                 | 10   | 13   | 16   | 19   | 22   | 25   |
|                        | <b>MAXIMUM SPAN OF LINTEL (m)</b> |      |      |      |      |      |      |
| 100TFB                 | 2.2                               | 1.8* | 1.5* | 1.3* | 1.2* | 1.1* | 1.0* |
| 125TFB                 | 4.5                               | 3.6* | 3.1* | 2.8* | 2.5* | 2.3* | 2.1* |
| 150UB14.0              | 4.7                               | 3.8* | 3.3* | 3.0* | 2.7* | 2.5* | 2.4* |
| • 150UB18.0            | 6.1                               | 5.0* | 4.3* | 3.8* | 3.5* | 3.2* | 3.0* |
| 180UB16.1              | 5.6                               | 4.7* | 4.1* | 3.7* | 3.3* | 3.1* | 2.9* |
| 180UB18.1              |                                   | 5.2* | 4.5* | 4.1* | 3.7* | 3.4* | 3.2* |
| • 180UB22.2            |                                   | 6.4* | 5.5* | 4.9* | 4.5* | 4.1* | 3.9* |
| 200UB18.2              |                                   | 5.4* | 4.7* | 4.2* | 3.9* | 3.6* | 3.4* |
| 200UB22.3              |                                   |      | 6.2* | 5.6* | 5.1* | 4.8* | 4.5* |
| 200UB25.4              |                                   |      | 6.8* | 6.1* | 5.6* | 5.2* | 4.9* |
| • 200UB29.8            |                                   |      | 7.7* | 7.3* | 6.6* | 6.1* | 5.8* |
| 250UB25.7              |                                   |      | 6.8* | 6.1* | 5.6* | 5.2* | 4.9* |
| 250UB31.4              |                                   |      |      |      | 6.9* | 6.5* | 6.1* |
| 250UB37.3              |                                   |      |      |      | 8.3* | 7.7* | 7.2* |
| 310UB32.0              |                                   |      |      |      | 7.1* | 6.6* | 6.3* |
| 310UB40.4              |                                   |      |      |      |      |      | 8.1* |
| 75PFC                  | 2.0                               | 1.6* | 1.3* | 1.1* |      |      |      |
| 100PFC                 | 3.0                               | 2.4* | 2.1* | 1.8* | 1.6* | 1.4* | 1.4* |
| 125PFC                 | 4.6                               | 3.7* | 3.2* | 2.8* | 2.5* | 2.3* | 2.2* |
| 150PFC                 |                                   | 5.6* | 4.8* | 4.3* | 3.9* | 3.5* | 3.3* |
| 180PFC                 |                                   | 6.6* | 5.7* | 5.0* | 4.6* | 4.2* | 3.9* |
| 200PFC                 |                                   |      | 6.2* | 5.5* | 5.0* | 4.6* | 4.3* |
| 230PFC                 |                                   |      | 6.6* | 5.9* | 5.3* | 4.9* | 4.6* |
| 250PFC                 |                                   |      |      |      | 7.9* | 7.2* | 6.8* |
| 300PFC                 |                                   |      |      |      |      |      | 7.5* |

**Example:**  
Refer to Fig. page 16  
Span=6.1m  
A=8.4m  
B=7.0  
Load area =0.3xAxB  
=0.3x8.4x7.0  
=17.6m<sup>2</sup>  
Use a load area of 19  
sq metres in the adjacent table  
a 200UB29.8 will span 6.6m  
and requires a M10 anchor rod.

**LINTEL SUPPORTING A STRUTTING BEAM, TILED ROOF AND CEILING - NORMAL WIND N3**

| Section<br>Designation | Load Area (m <sup>2</sup> )       |      |      |      |      |      |      |
|------------------------|-----------------------------------|------|------|------|------|------|------|
|                        | 7                                 | 10   | 13   | 16   | 19   | 22   | 25   |
|                        | <b>MAXIMUM SPAN OF LINTEL (m)</b> |      |      |      |      |      |      |
| 100TFB                 | 2.7                               | 2.1  | 1.6* | 1.3* | 1.1* |      |      |
| 125TFB                 | 4.1                               | 3.7  | 3.5* | 3.1* | 2.5* | 2.2* | 2.0* |
| 150UB14.0              | 4.8                               | 4.3  | 3.9* | 3.7* | 3.3* | 2.7* | 2.5* |
| • 150UB18.0            | 5.3                               | 4.8  | 4.4* | 4.1* | 4.0* | 3.7* | 3.3* |
| 180UB16.1              | 5.5                               | 5.0  | 4.7* | 4.2* | 4.1* | 3.8* | 3.4* |
| 180UB18.1              | 5.8                               | 5.3  | 4.9* | 4.6* | 4.4* | 4.2* | 3.8* |
| • 180UB22.2            | 6.2                               | 5.7  | 5.3* | 4.9* | 4.7* | 4.5* | 4.3* |
| 200UB18.2              | 6.3                               | 5.7  | 5.3* | 4.9* | 4.7* | 4.1* | 4.1* |
| 200UB22.3              |                                   | 6.3  | 5.8* | 5.5* | 5.2* | 4.9* | 4.8* |
| 200UB25.4              |                                   | 6.5  | 6.0* | 5.7* | 5.4* | 5.1* | 5.0* |
| • 200UB29.8            |                                   | 6.9  | 6.5* | 6.1* | 5.7* | 5.5* | 5.3* |
| 250UB25.7              |                                   | 7.4  | 6.9* | 6.5* | 6.1* | 5.9* | 5.7* |
| 250UB31.4              |                                   |      | 7.4* | 7.0* | 6.6* | 6.3* | 6.1* |
| 250UB37.3              |                                   |      | 7.9* | 7.5* | 7.1* | 6.8* | 6.6* |
| 310UB32.0              |                                   |      | 8.3* | 7.8* | 7.4* | 7.1* | 6.9* |
| 310UB40.4              |                                   |      |      |      | 8.2* | 7.8* | 7.6* |
| 310UB46.2              |                                   |      |      |      | 8.5* | 8.2* | 7.9* |
| 75PFC                  | 1.8                               | 1.3  | 1.0* |      |      |      |      |
| 100PFC                 | 2.8                               | 2.4  | 1.8* | 1.5* | 1.3* | 1.1* |      |
| 125PFC                 | 4.0                               | 3.6  | 3.3* | 2.7* | 2.3* | 2.0* | 1.8* |
| 150PFC                 | 5.1                               | 4.6  | 4.3* | 4.0* | 3.8* | 3.5* | 3.1* |
| 180PFC                 | 6.1                               | 5.5* | 5.1* | 4.8* | 4.5* | 4.3* | 4.1* |
| 200PFC                 |                                   | 6.1* | 5.6* | 5.3* | 5.0* | 4.8* | 4.6* |
| 230PFC                 |                                   | 6.8* | 6.3* | 5.9* | 5.6* | 5.4* | 5.2* |
| 250PFC                 |                                   |      | 7.4* | 7.0* | 6.6* | 6.3* | 6.1* |
| 300PFC                 |                                   |      |      | 8.1* | 7.7* | 7.4* | 7.1* |


**Example:**  
Refer to Fig. page 16  
Span=6.1m  
A=8.4m  
B=7.0m  
Load area =0.3xAxB  
=0.3x8.4x7.0  
=17.6m<sup>2</sup>  
Use a load area of 19  
sq metres in the adjacent table  
a 250UB25.7 will span 6.1m  
and requires a M10 anchor rod.

**Notes on Tables:**

- The tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
- For sections marked '•' the next largest size may be more economical.
- No symbol next to the span indicates that only nominal holding down is required (uplift is less than 5 kN).  
A "\*" indicates a M10 holding down rod is required (uplift is between 5 and 19 kN).

# VERANDAH BEAMS

|   | Load (kg/m <sup>2</sup> ) |   | Deflection Limit (mm) |                   |
|---|---------------------------|---|-----------------------|-------------------|
|   | Dead Load                 | Live Load                               | Dead & Live Load      | Live Load         |
| Beams supporting a steel sheet verandah roof or carport | 40                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/240<br>to 15     | span/360<br>to 10 |
| Beams supporting a tiled verandah roof or carport       | 90                        | 25<br>(or $\geq 180/\text{Area} + 12$ ) | span/240<br>to 15     | span/360<br>to 10 |



**Notes:**

1. The top flange of the Beam is assumed to be continuously laterally supported by rafters at 900mm maximum centres.

**BEAM SUPPORTING A STEEL SHEET VERANDAH OR CARPORT ROOF - NORMAL WIND N3**

| Section<br>Designation          | Load Width (m) |      |      |      |      |      |      |
|---------------------------------|----------------|------|------|------|------|------|------|
|                                 | 1.2            | 1.8  | 2.4  | 3.0  | 3.6  | 4.2  | 4.8  |
| <b>MAXIMUM SPAN OF BEAM (m)</b> |                |      |      |      |      |      |      |
| 100TFB                          | 3.2            | 2.8* | 2.5* | 2.3* | 2.1* | 2.0* | 1.9* |
| 125TFB                          | 5.0*           | 4.3* | 3.9* | 3.6* | 3.4* | 3.2* | 3.0* |
| 150UB14.0                       | 5.2*           | 4.5* | 4.0* | 3.7* | 3.5* | 3.3* | 3.2* |
| • 150UB18.0                     | 6.1*           | 5.3* | 4.8* | 4.4* | 4.1* | 3.9* | 3.7* |
| 180UB16.1                       | 5.8*           | 5.1* | 4.6* | 4.2* | 4.0* | 3.8* | 3.6* |
| 180UB18.1                       |                | 5.5* | 4.9* | 4.6* | 4.3* | 4.1* | 3.9+ |
| • 180UB22.2                     |                | 6.2* | 5.6* | 5.2* | 4.8* | 4.6+ | 4.4+ |
| 200UB18.2                       |                | 5.6* | 5.0* | 4.7* | 4.4* | 4.2* | 4.0+ |
| 200UB22.3                       |                | 6.7* | 6.1* | 5.6* | 5.3+ | 5.0+ | 4.8+ |
| 200UB25.4                       |                | 7.1* | 6.5* | 6.0* | 5.6+ | 5.3+ | 5.1+ |
| • 200UB29.8                     |                | 8.0* | 7.2* | 6.7+ | 6.3+ | 5.9+ | 5.6^ |
| 250UB25.7                       |                | 7.1* | 6.4* | 6.0* | 5.6+ | 5.3+ | 5.1+ |
| 250UB31.4                       |                |      | 7.4* | 6.9+ | 6.5+ | 6.2+ | 5.9^ |
| • 250UB37.3                     |                |      | 8.4+ | 7.7+ | 7.3+ | 6.9^ | 6.6^ |
| 310UB32.0                       |                |      | 7.5* | 7.0+ | 6.6+ | 6.3+ | 6.0^ |
| 310UB40.4                       |                |      |      | 8.3+ | 7.9^ | 7.5^ | 7.1^ |
| 310UB46.2                       |                |      |      |      | 8.5^ | 8.0^ | 7.7^ |
| 75PFC                           | 3.1            | 2.6  | 2.4* | 2.2* | 2.0* | 1.9* | 1.8* |
| 100PFC                          | 3.9            | 3.4* | 3.0* | 2.8* | 2.6* | 2.5* | 2.3* |
| 125PFC                          | 5.1*           | 4.4* | 4.0* | 3.7* | 3.4* | 3.2* | 3.1* |
| 150PFC                          |                | 5.7* | 5.2* | 4.8* | 4.4* | 4.2* | 4.0+ |
| 180PFC                          |                | 6.4* | 5.7* | 5.3* | 4.9* | 4.7+ | 4.4+ |
| 200PFC                          |                | 6.7* | 6.1* | 5.6* | 5.2+ | 4.9+ | 4.7+ |
| 230PFC                          |                | 7.0* | 6.3* | 5.8* | 5.4+ | 5.1+ | 4.9+ |
| 250PFC                          |                |      |      | 7.5+ | 7.0+ | 6.6^ | 6.3^ |
| 300PFC                          |                |      |      | 8.0+ | 7.4+ | 7.0^ | 6.7^ |

**Example:**  
Refer to Fig. page 18  
Span=6.1m  
A=7.0m, B=6.1m  
Load width=A<sup>2</sup>/2B  
=7.0<sup>2</sup>/(2x6.1)  
=4.0m  
Use a load width of 4.2  
in the adjacent table  
a 250UB31.4 will span 6.2m  
and requires a M12 anchor rod.

**BEAM SUPPORTING A TILED VERANDAH OR CARPORT ROOF - NORMAL WIND N3**

| Section<br>Designation          | Load Width (m) |      |      |      |      |      |      |
|---------------------------------|----------------|------|------|------|------|------|------|
|                                 | 1.2            | 1.8  | 2.4  | 3.0  | 3.6  | 4.2  | 4.8  |
| <b>MAXIMUM SPAN OF BEAM (m)</b> |                |      |      |      |      |      |      |
| 100TFB                          | 3.8            | 3.4  | 3.2  | 3.0  | 2.8  | 2.6* | 2.4* |
| 125TFB                          | 5.0            | 4.6  | 4.3  | 4.1* | 3.9* | 3.8* | 3.7* |
| 150UB14.0                       | 5.6            | 5.1  | 4.8* | 4.6* | 4.4* | 4.2* | 4.1* |
| • 150UB18.0                     | 6.0            | 5.5  | 5.2* | 4.9* | 4.7* | 4.5* | 4.4* |
| 180UB16.1                       | 6.3            | 5.8  | 5.4* | 5.1* | 4.9* | 4.7* | 4.6* |
| 180UB18.1                       | 6.5            | 5.9  | 5.6* | 5.3* | 5.1* | 4.9* | 4.7* |
| • 180UB22.2                     | 6.8            | 6.3  | 5.9* | 5.6* | 5.4* | 5.2* | 5.0* |
| 200UB18.2                       | 6.9            | 6.4  | 6.0* | 5.7* | 5.4* | 5.2* | 5.1* |
| 200UB22.3                       | 7.4            | 6.8* | 6.4* | 6.1* | 5.8* | 5.6* | 5.4* |
| 200UB25.4                       | 7.6            | 7.0* | 6.6* | 6.2* | 6.0* | 5.8* | 5.6* |
| • 200UB29.8                     | 8.0            | 7.4* | 6.9* | 6.6* | 6.3* | 6.1* | 5.9* |
| 250UB25.7                       | 8.4            | 7.8* | 7.3* | 6.9* | 6.6* | 6.4* | 6.2* |
| 250UB31.4                       |                | 8.2* | 7.7* | 7.3* | 7.0* | 6.7* | 6.5* |
| • 250UB37.3                     |                | 8.6* | 8.1* | 7.7* | 7.4* | 7.1* | 6.9* |
| 310UB32.0                       |                | 8.9* | 8.4* | 8.0* | 7.6* | 7.4* | 7.1* |
| 310UB40.4                       |                |      | 9.0* | 8.6* | 8.2* | 7.9* | 7.7* |
| 310UB46.2                       |                |      | 9.3* | 8.8* | 8.5* | 8.2* | 8.0* |
| 75PFC                           | 2.9            | 2.6  | 2.4  | 2.3  | 2.1  | 2.0  | 2.0  |
| 100PFC                          | 3.9            | 3.6  | 3.4  | 3.1  | 3.0  | 2.8* | 2.7* |
| 125PFC                          | 4.9            | 4.5  | 4.2  | 4.0* | 3.8* | 3.7* | 3.6* |
| 150PFC                          | 5.9            | 5.4  | 5.1* | 4.8* | 4.6* | 4.4* | 4.3* |
| 180PFC                          | 6.7            | 6.2  | 5.8* | 5.5* | 5.3* | 5.1* | 4.9* |
| 200PFC                          | 7.2            | 6.6* | 6.2* | 5.9* | 5.7* | 5.5* | 5.3* |
| 230PFC                          | 7.8            | 7.2* | 6.8* | 6.4* | 6.2* | 6.0* | 5.8* |
| 250PFC                          |                | 8.2* | 7.7* | 7.3* | 7.0* | 6.7* | 6.5* |
| 300PFC                          |                |      | 8.6* | 8.2* | 7.9* | 7.6* | 7.4* |

**Example:**  
Refer to Fig. page 18  
Required beam span=4.0m  
A=6.0m  
B=5.1m  
Load width=A<sup>2</sup>/2B  
=6.0<sup>2</sup>/(2x5.1)  
=3.5m  
Use a load width of 3.6  
in the adjacent table  
a 150UB14.0 will span 4.4m  
and requires a M10 anchor rod.

**Notes on Tables:**

- The Tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
- For sections marked '•' the next largest size may be more economical.
- No symbol next to the span indicates that only nominal holding down is required (uplift is less than 5 kN). A "\*" indicates a M10 holding down rod is required (uplift is between 5 and 19 kN). A "+" indicates a M12 holding down bolt is required (uplift is between 19 & 27 kN). A "^" indicates a M16 holding down bolt is required (uplift is between 27 and 50 kN).
- For a steel sheet roof in high wind load areas refer to table on page 21.

# STEEL SHEET ROOFS IN HIGH WIND AREAS

## STRUTTING BEAM SUPPORTING A STEEL SHEET ROOF AND CEILING - HIGH WIND N5/C2

| Section<br>Designation   | Load Area (m <sup>2</sup> ) |      |      |      |      |      |      | Refer to page 8 for<br>the layout diagram   |
|--------------------------|-----------------------------|------|------|------|------|------|------|---|
|                          | 7                           | 10   | 13   | 16   | 19   | 22   | 25   |   |
| MAXIMUM SPAN OF BEAM (m) |                             |      |      |      |      |      |      |   |
| 100TFB                   | 1.7*                        | 1.1* |      |      |      |      |      | <p>Example:<br/>Refer to Fig. page 8<br/>Span S=6.1m<br/>A=7.0m<br/>Load area=0.25xAxS<br/>=0.25x7.0x6.1<br/>=10.7m<sup>2</sup><br/>Use a load area of 13<br/>sq metres in the adjacent table<br/>a 200UB22.3 will span 6.1m<br/>and requires a M12 anchor rod.</p> |
| 125TFB                   | 4.0*                        | 2.8* | 2.1+ | 1.7+ | 1.4^ | 1.2^ | 1.1^ |   |
| 150UB14.0                | 4.4*                        | 3.6* | 2.7+ | 2.2+ | 1.8^ | 1.6^ | 1.4^ |   |
| • 150UB18.0              | 5.6*                        | 4.6* | 3.6+ | 2.9+ | 2.5^ | 2.1^ | 1.9^ |   |
| 180UB16.1                | 5.5*                        | 4.5* | 3.7+ | 3.0+ | 2.5^ | 2.2^ | 1.9^ |   |
| 180UB18.1                | 6.1*                        | 5.0* | 4.2+ | 3.4+ | 2.9^ | 2.5^ | 2.2^ |   |
| • 180UB22.2              | 7.3*                        | 6.0* | 5.1+ | 4.3+ | 3.6^ | 3.1^ | 2.7^ |   |
| 200UB18.2                | 6.4*                        | 5.3* | 4.6+ | 3.9+ | 3.3^ | 2.8^ | 2.5^ |   |
| 200UB22.3                |                             | 7.1* | 6.1+ | 5.0+ | 4.2^ | 3.6^ | 3.2^ |   |
| 200UB25.4                |                             | 7.7* | 6.6+ | 5.7+ | 4.8^ | 4.1^ | 3.7^ |   |
| • 200UB29.8              |                             | 8.9* | 7.7+ | 6.9^ | 5.9^ | 5.0^ | 4.5^ |   |
| 250UB25.7                |                             | 7.9* | 6.9+ | 6.2+ | 5.6^ | 5.1^ | 4.5^ |   |
| 250UB31.4                |                             |      | 8.5+ | 7.6+ | 6.9^ | 6.3^ | 5.6^ |   |
| • 250UB37.3              |                             |      | 9.9+ | 8.9+ | 8.1^ | 7.4^ | 6.9^ |   |
| 310UB32.0                |                             |      | 8.9+ | 8.0+ | 7.4^ | 6.8^ | 6.5^ |   |
| 310UB40.4                |                             |      |      |      | 9.4^ | 8.7^ | 8.2^ |   |
| 310UB46.2                |                             |      |      |      |      | 9.5^ | 8.9^ |   |
| 75PFC                    | 1.0                         |      |      |      |      |      |      |   |
| 100PFC                   | 2.0*                        | 1.4* | 1.0+ |      |      |      |      |   |
| 125PFC                   | 3.6*                        | 2.5* | 1.9+ | 1.6+ | 1.3^ | 1.1^ | 1.0^ |   |
| 150PFC                   | 6.2*                        | 4.5* | 3.5+ | 2.8+ | 2.3^ | 2.0^ | 1.8^ |   |
| 180PFC                   | 7.4*                        | 6.0* | 4.6+ | 3.7+ | 3.1^ | 2.7^ | 2.4^ |   |
| 200PFC                   |                             | 6.6* | 5.6+ | 4.5+ | 3.8^ | 3.3^ | 2.9^ |   |
| 230PFC                   |                             | 7.2* | 6.2+ | 5.4+ | 4.7^ | 4.0^ | 3.6^ |   |
| 250PFC                   |                             |      | 9.0+ | 7.9+ | 7.1^ | 6.8^ | 5.6^ |   |
| 300PFC                   |                             |      |      | 9.0+ | 8.2^ | 7.5^ | 7.0^ |   |

## STRUTTING/HANGING BEAM SUPPORTING A STEEL SHEET ROOF AND CEILING - HIGH WIND N5/C2

| Section<br>Designation   | Load Width (m) |      |      |      |      |      |      | Refer to page 10 for<br>the layout diagram  |
|--------------------------|----------------|------|------|------|------|------|------|---|
|                          | 1.2            | 1.8  | 2.4  | 3.0  | 3.6  | 4.2  | 4.8  |   |
| MAXIMUM SPAN OF BEAM (m) |                |      |      |      |      |      |      |   |
| 100TFB                   | 2.7*           | 2.3* | 2.1* | 2.0* | 1.8* | 1.7* | 1.7* | <p>Example:<br/>Refer to Fig. page 10<br/>Span=4.6m<br/>A=3.0m<br/>B=2.9m<br/>Load width=0.5A<br/>=0.5x3.0<br/>=1.5<br/>Use a load width of 1.8<br/>in the adjacent table<br/>a 200UB18.2 will span 4.6m<br/>and requires a M10 anchor rod.</p> |
| 125TFB                   | 4.2*           | 3.7* | 3.3* | 3.1* | 2.9* | 2.7+ | 2.6+ |   |
| 150UB14.0                | 4.3*           | 3.7* | 3.4* | 3.2* | 3.0* | 2.8+ | 2.7+ |   |
| • 150UB18.0              | 5.0*           | 4.4* | 4.0* | 3.7* | 3.5+ | 3.3+ | 3.2+ |   |
| 180UB16.1                | 4.8*           | 4.2* | 3.8* | 3.6* | 3.4+ | 3.2+ | 3.1+ |   |
| 180UB18.1                | 5.1*           | 4.5* | 4.1* | 3.8* | 3.6+ | 3.4+ | 3.3+ |   |
| • 180UB22.2              | 5.8*           | 5.1* | 4.7* | 4.4+ | 4.1+ | 3.9+ | 3.7^ |   |
| 200UB18.2                | 5.2*           | 4.6* | 4.2* | 3.9+ | 3.7+ | 3.5+ | 3.3+ |   |
| 200UB22.3                | 6.2*           | 5.5* | 5.0+ | 4.7+ | 4.4+ | 4.2^ | 4.0^ |   |
| 200UB25.4                | 6.6*           | 5.8* | 5.3+ | 5.0+ | 4.7^ | 4.5^ | 4.3^ |   |
| • 200UB29.8              | 7.4*           | 6.5* | 6.0+ | 5.5+ | 5.2^ | 5.0^ | 4.8^ |   |
| 250UB25.7                | 6.5*           | 5.8* | 5.3+ | 4.9+ | 4.7^ | 4.4^ | 4.3^ |   |
| 250UB31.4                |                | 6.6* | 6.1+ | 5.7^ | 5.3^ | 5.1^ | 4.9^ |   |
| • 250UB37.3              |                | 7.4+ | 6.8+ | 6.4^ | 6.0^ | 5.7^ | 5.5^ |   |
| 310UB32.0                |                | 6.6* | 6.1+ | 5.7^ | 5.4^ | 5.2^ | 5.0^ |   |
| 310UB40.4                |                | 7.9+ | 7.3^ | 6.8^ | 6.4^ | 6.1^ | 5.9^ |   |
| 310UB46.2                |                |      | 7.8^ | 7.3^ | 6.9^ | 6.6^ | 6.3^ |   |
| 75PFC                    | 2.7*           | 2.3* | 2.1* | 1.9* | 1.8* | 1.7* | 1.6* |   |
| 100PFC                   | 3.3*           | 2.9* | 2.6* | 2.4* | 2.3* | 2.1* | 2.0* |   |
| 125PFC                   | 4.3*           | 3.7* | 3.4* | 3.1* | 2.9* | 2.8+ | 2.7+ |   |
| 150PFC                   | 5.5*           | 4.8* | 4.4* | 4.1+ | 3.8+ | 3.6+ | 3.4^ |   |
| 180PFC                   | 6.0*           | 5.3* | 4.8* | 4.5+ | 4.2+ | 4.0^ | 3.8^ |   |
| 200PFC                   | 6.3*           | 5.6* | 5.1+ | 4.7+ | 4.4+ | 4.2^ | 4.0^ |   |
| 230PFC                   | 6.5*           | 5.7* | 5.2+ | 4.9+ | 4.6+ | 4.3^ | 4.2^ |   |
| 250PFC                   |                | 7.3+ | 6.7+ | 6.2^ | 5.8^ | 5.6^ | 5.3^ |   |
| 300PFC                   |                | 7.7+ | 7.0+ | 6.6^ | 6.2^ | 5.9^ | 5.6^ |   |

### LINTEL SUPPORTING A STEEL SHEET ROOF AND CEILING - HIGH WIND N5/C2

| Section<br>Designation     | Load Width (m) |      |      |      |      |      |      | Refer to page 12 for<br>the layout diagram  |
|----------------------------|----------------|------|------|------|------|------|------|---|
|                            | 1.2            | 1.8  | 2.4  | 3.0  | 3.6  | 4.8  | 6.0  |   |
| MAXIMUM SPAN OF LINTEL (m) |                |      |      |      |      |      |      |   |
| 100TFB                     | 2.7*           | 2.3* | 2.1* | 1.9* | 1.8* | 1.6* | 1.5* | <b>Example:</b><br>Refer to Fig. page 12<br>Lintel Span=4.6m, trussed roof<br>A=3.8m<br>Load width=A<br>=3.8m<br>Use a load width of 4.8<br>in the adjacent table<br>a 250UB29.8 will span 4.8m<br>and requires a M16 anchor rod. |
| 125TFB                     | 4.3*           | 3.7* | 3.3* | 3.0* | 2.8* | 2.5+ | 2.3+ |   |
| 150UB14.0                  | 4.4*           | 3.8* | 3.4* | 3.2* | 3.0* | 2.7+ | 2.5+ |   |
| • 150UB18.0                | 5.2*           | 4.5* | 4.1* | 3.7* | 3.5+ | 3.1+ | 2.9^ |   |
| 180UB16.1                  | 5.0*           | 4.3* | 3.9* | 3.6* | 3.4+ | 3.1+ | 2.9^ |   |
| 180UB18.1                  | 5.4*           | 4.7* | 4.2* | 3.9+ | 3.6+ | 3.3+ | 3.0^ |   |
| • 180UB22.2                | 6.1*           | 5.3* | 4.8* | 4.4+ | 4.1+ | 3.7^ | 3.4^ |   |
| 200UB18.2                  | 5.5*           | 4.8* | 4.3* | 4.0+ | 3.8+ | 3.4^ | 3.2^ |   |
| 200UB22.3                  | 6.6*           | 5.7* | 5.2+ | 4.8+ | 4.5+ | 4.1^ | 3.8^ |   |
| 200UB25.4                  | 7.0*           | 6.1* | 5.5+ | 5.1+ | 4.8^ | 4.3^ | 4.0^ |   |
| • 200UB29.8                | 7.9*           | 6.8+ | 6.1+ | 5.7^ | 5.3^ | 4.8^ | 4.4^ |   |
| 250UB25.7                  | 7.0*           | 6.1* | 5.5+ | 5.1+ | 4.8^ | 4.4^ | 4.1^ |   |
| 250UB31.4                  |                | 7.0+ | 6.4+ | 5.9^ | 5.6^ | 5.1^ | 4.7^ |   |
| • 250UB37.3                |                | 7.9+ | 7.1^ | 6.6^ | 6.2^ | 5.6^ | 5.2^ |   |
| 75PFC                      | 2.6*           | 2.2* | 2.0* | 1.8* | 1.7* | 1.5* | 1.4* |   |
| 100PFC                     | 3.3*           | 2.9* | 2.6* | 2.3* | 2.2* | 2.0* | 1.8* |   |
| 125PFC                     | 4.3*           | 3.7* | 3.3* | 3.1* | 2.9* | 2.6+ | 2.4+ |   |
| 150PFC                     | 5.6*           | 4.9* | 4.4* | 4.0+ | 3.7+ | 3.4+ | 3.1^ |   |
| 180PFC                     | 6.2*           | 5.4* | 4.8* | 4.5+ | 4.2+ | 3.7^ | 3.4^ |   |
| 200PFC                     | 6.6*           | 5.7* | 5.1+ | 4.7+ | 4.4+ | 4.0^ | 3.7^ |   |
| 230PFC                     | 6.8*           | 5.9* | 5.3+ | 4.9+ | 4.6^ | 4.2^ | 3.8^ |   |
| 250PFC                     |                | 7.6+ | 6.8+ | 6.3^ | 5.9^ | 5.3^ | 4.9^ |   |

### BEAM SUPPORTING A STEEL SHEET VERANDAH OR CARPORT ROOF - HIGH WIND N5/C2

| Section<br>Designation   | Load Width (m) |      |      |      |      |      |      | Refer to page 18 for<br>the layout diagram   |
|--------------------------|----------------|------|------|------|------|------|------|--|
|                          | 1.2            | 1.8  | 2.4  | 3.0  | 3.6  | 4.2  | 4.8  |  |
| MAXIMUM SPAN OF BEAM (m) |                |      |      |      |      |      |      |  |
| 100TFB                   | 2.7*           | 2.3* | 2.1* | 1.9* | 1.8* | 1.7* | 1.6* | <b>Example:</b><br>Refer to Fig. page 18<br>Span=4.6m<br>A=3.8m<br>B=3.0m<br>Load width =A <sup>2</sup> /2B<br>=3.8 <sup>2</sup> /(2x3.0)<br>=2.4m<br>Use a load width of 2.4<br>in the adjacent table<br>a 180UB22.2 will span 4.8m<br>and requires a M10 anchor rod. |
| 125TFB                   | 4.3*           | 3.7* | 3.3* | 3.0* | 2.8* | 2.7* | 2.5+ |  |
| 150UB14.0                | 4.4*           | 3.8* | 3.4* | 3.2* | 3.0* | 2.8+ | 2.7+ |  |
| • 150UB18.0              | 5.2*           | 4.5* | 4.1* | 3.7* | 3.5+ | 3.3+ | 3.1+ |  |
| 180UB16.1                | 5.0*           | 4.3* | 3.9* | 3.6* | 3.4+ | 3.2+ | 3.1+ |  |
| 180UB18.1                | 5.4*           | 4.7* | 4.2* | 3.9+ | 3.6+ | 3.5+ | 3.3+ |  |
| • 180UB22.2              | 6.1*           | 5.3* | 4.8* | 4.4+ | 4.1+ | 3.9+ | 3.7^ |  |
| 200UB18.2                | 5.5*           | 4.8* | 4.3* | 4.0+ | 3.8+ | 3.6+ | 3.4^ |  |
| 200UB22.3                | 6.6*           | 5.7* | 5.2+ | 4.8+ | 4.5+ | 4.3^ | 4.1^ |  |
| 200UB25.4                | 7.0*           | 6.1* | 5.5+ | 5.1+ | 4.8^ | 4.5^ | 4.3^ |  |
| • 200UB29.8              | 7.9*           | 6.8+ | 6.1+ | 5.7^ | 5.3^ | 5.0^ | 4.8^ |  |
| 250UB25.7                | 7.0*           | 6.1* | 5.5+ | 5.1+ | 4.8^ | 4.6^ | 4.4^ |  |
| 250UB31.4                |                | 7.0+ | 6.4+ | 5.9^ | 5.6^ | 5.3^ | 5.1^ |  |
| • 250UB37.3              |                | 7.9+ | 7.1^ | 6.6^ | 6.2^ | 5.9^ | 5.6^ |  |
| 310UB32.0                |                | 7.1+ | 6.5+ | 6.0^ | 5.7^ | 5.4^ | 5.2^ |  |
| 310UB40.4                |                | 8.5+ | 7.7^ | 7.2^ | 6.7^ | 6.4^ | 6.1^ |  |
| 310UB46.2                |                |      | 8.3^ | 7.7^ | 7.2^ | 6.9^ |      |  |
| 75PFC                    | 2.6*           | 2.2* | 2.0* | 1.8* | 1.7* | 1.6* | 1.5* |  |
| 100PFC                   | 3.3*           | 2.9* | 2.6* | 2.3* | 2.2* | 2.1* | 2.0* |  |
| 125PFC                   | 4.3*           | 3.7* | 3.3* | 3.1* | 2.9* | 2.7* | 2.6+ |  |
| 150PFC                   | 5.6*           | 4.9* | 4.4* | 4.0+ | 3.7+ | 3.5+ | 3.4+ |  |
| 180PFC                   | 6.2*           | 5.4* | 4.8* | 4.5+ | 4.2+ | 3.9^ | 3.7^ |  |
| 200PFC                   | 6.6*           | 5.7* | 5.1+ | 4.7+ | 4.4+ | 4.2^ | 4.0^ |  |
| 230PFC                   | 6.8*           | 5.9* | 5.3+ | 4.9+ | 4.6^ | 4.4^ | 4.2^ |  |
| 250PFC                   |                | 7.6+ | 6.8+ | 6.3^ | 5.9^ | 5.6^ | 5.3^ |  |
| 300PFC                   |                | 8.1+ | 7.3^ | 6.8^ | 6.3^ | 6.0^ | 5.7^ |  |



#### Notes on Tables:

- The tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
- For angle lintels, the first dimension corresponds to the vertical lintel leg. eg for 100x75x6UA, 100mm leg is vertical.
- For sections marked '•' the next largest size may be more economical.
- No symbol next to the span indicates that only nominal holding down is required (uplift is less than 5 kN).  
 A "\*" indicates a M10 holding down rod is required (uplift is between 5 and 19 kN).  
 A "+" indicates a M12 holding down bolt is required (uplift is between 19 and 27 kN).  
 A "^" indicates a M16 holding down bolt is required (uplift is between 27 and 50 kN).

# LINTELS SUPPORTING MASONRY


These span tables provide details for building houses using standard practices and traditional materials.

- ◆ Point loads are not covered by these tables.
- ◆ These tables cover normal loads (roof, ceiling and floors), which must be uniformly distributed, on the masonry over an opening.
- ◆ A minimum of three courses of brickwork are required over the opening for load bearing walls.
- ◆ For lintels to be used in a lower floor of two storey construction refer to a structural engineer.




## CONSTRUCTION TYPES

Illustrations of construction types A, B, C and D refer to the maximum clear span loading on the tables opposite.



### Construction Type A:

Typical brick veneer construction with non load bearing brickwork and roof supported on internal timber or steel timber.




### Construction Type B:

Cavity wall construction with timber or steel truss tiled roof supported equally on both leaves of brickwork.



### Construction Type C:

Light weight metal sheet roof supported on single leaf of brickwork.



### Construction Type D:

Tiled roof with timber or steel truss and sheet ceiling supported on single leaf of brickwork.

### LINTEL SUPPORTING MASONRY - LOAD WIDTH UP TO 2400mm

| Steel Lintel                             | Mass (kg/m) | Construction type |      |      |      |
|--|-------------|-------------------|------|------|------|
|  |             | A                 | B    | C    | D    |
| <b>MAXIMUM CLEAR SPAN OF LINTEL (mm)</b> |             |                   |      |      |      |
| 75 x 75 x 6EA                            | 6.81        | 2650              | 1930 | 1930 | 1570 |
| # 75 x 100 x 6UA                         | 7.98        | 2770              | 2050 | 2050 | 1690 |
| # 75 x 100 x 8UA                         | 10.3        | 2770              | 2170 | 2170 | 1810 |
| 90 x 90 x 6EA                            | 8.22        | 3010              | 2410 | 2410 | 1930 |
| 100 x 75 x 6UA                           | 7.98        | 3010              | 2530 | 2530 | 2170 |
| 90 x 90 x 8EA                            | 10.6        | 3010              | 2530 | 2530 | 2170 |
| 100 x 100 x 6EA                          | 9.16        | 3130              | 2530 | 2650 | 2170 |
| 100 x 100 x 8EA                          | 11.8        | 3370              | 2770 | 2770 | 2410 |
| 125 x 75 x 6UA                           | 9.16        | 3610              | 3010 | 3010 | 2650 |
| 125 x 75 x 8UA                           | 11.8        | 3730              | 3130 | 3250 | 2770 |
| 150 x 90 x 8UA                           | 14.3        | 4210              | 3610 | 3730 | 3250 |
| 150 x 100 x 10UA                         | 18.0        | 4330              | 3850 | 3850 | 3490 |
| Square Edge Flats                        |             |                   |      |      |      |
| 75 x 8SEF                                |             | 490               | 250  |      |      |
| 75 x 10SEF                               |             | 610               | 370  | 250  | 250  |

### LINTEL SUPPORTING MASONRY - LOAD WIDTH FROM 2400mm TO 4800mm

| Steel Lintel                             | Mass (kg/m) | Construction type |      |      |      |
|--|-------------|-------------------|------|------|------|
|  |             | A                 | B    | C    | D    |
| <b>MAXIMUM CLEAR SPAN OF LINTEL (mm)</b> |             |                   |      |      |      |
| 75 x 75 x 6EA                            | 6.81        | 2650              | 1690 | 1690 | 1330 |
| # 75 x 100 x 6UA                         | 7.98        | 2770              | 1690 | 1690 | 1330 |
| # 75 x 100 x 8UA                         | 10.3        | 2770              | 1810 | 1810 | 1450 |
| 90 x 90 x 6EA                            | 8.22        | 3010              | 2050 | 2050 | 1570 |
| 100 x 75 x 6UA                           | 7.98        | 3010              | 2170 | 2170 | 1690 |
| 90 x 90 x 8EA                            | 10.6        | 3010              | 2170 | 2170 | 1810 |
| 100 x 100 x 6EA                          | 9.16        | 3130              | 2290 | 2290 | 1810 |
| 100 x 100 x 8EA                          | 11.8        | 3370              | 2410 | 2410 | 1930 |
| 125 x 75 x 6UA                           | 9.16        | 3610              | 2530 | 2650 | 2050 |
| 125 x 75 x 8UA                           | 11.8        | 3730              | 2770 | 2890 | 2410 |
| 150 x 90 x 8UA                           | 14.3        | 4210              | 3370 | 3370 | 2770 |
| 150 x 100 x 10UA                         | 8.0         | 4330              | 3490 | 3610 | 3010 |
| Square Edge Flats                        |             |                   |      |      |      |
| 75 x 8SEF                                |             | 490               | 250  |      |      |
| 75 x 10SEF                               |             | 610               | 250  | 250  | 250  |

# Section with short leg vertical for wide base support of brickwork.


#### Notes on Tables:

1. The tables apply for 300PLUS® steel only. For details of your nearest 300PLUS® structural steel supplier, call OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335), or visit our website at [www.onesteel.com](http://www.onesteel.com)
2. For Clear span  $\leq$  1000mm, Min Bearing Length = 100mm, ie. Min Lintel Length = Clear Span + 200mm.  
For Clear span > 1000mm, Min Bearing Length = 150mm, ie. Min Lintel Length = Clear Span + 300mm.
3. All lintels should be propped during brickwork construction to ensure level alignment.
4. The maximum rafter spacing should not be greater than 600mm.
5. There must be at least three courses of brickwork over clear span opening for all load bearing walls.
6. All loads are uniformly distributed (point loads are not allowed).
7. First dimension corresponds to the vertical lintel leg, eg. 75x100x6 lintel, 75mm leg vertical.


# CONNECTION EXAMPLES


The following diagrams provide some example arrangements for common connections using structural steel members. Please note that it is the reader's responsibility to ensure that all connections, including tie downs, are sufficient for the application.

## BEARERS





## STRUTTING BEAMS





## LINTELS



# SURFACE TREATMENT

The requirements for surface treatment vary with the location of the house and the degree of enclosure around the supporting steelwork.

For three sources of corrosion, and depending on whether the house is in an exposed or protected position, a level of corrosion potential may be established based on the distance of the house from the source of corrosion Figure 1, Table 1.

The degree of enclosure of the supporting steelwork must then be considered. If it is enclosed by masonry walls (which include provision for sub-floor ventilation) with a maximum size/area of openings as shown in Figure 2, it is deemed to be 'enclosed'. Otherwise it is deemed to be 'unenclosed'.

The required surface treatment for each level of corrosion potential and for 'enclosed' or 'unenclosed' steelwork can then be determined from Table 2. Finally, the required treatment can be determined from Table 3.

| Distance From Source of Corrosion:<br>Ocean OR Heavy industrial area | LEVELS OF SURFACE TREATMENT |                  |
|--|-----------------------------|------------------|
|  | House Site in:              |                  |
|  | Protected Position*         | Exposed Position |
| Over 3 km  | Level 1                     | Level 1          |
| 1.5–3 km   | Level 1                     | Level 2          |
| 0.75–1.5 km  | Level 2                     | Level 3          |
| Within 0.75 km   | Level 3                     | Level 3          |
| <b>Salt-water bay</b>  |                             |                  |
| Over 1.5 km  | Level 1                     | Level 1          |
| 0.75–1.5 km  | Level 1                     | Level 2          |
| Within 0.75 km   | Level 2                     | Level 2          |

\*A protected position is one that is more than 0.5 km from the nearest location that is in line of sight of the source of corrosion Figure 1.




Figure 1 Definition of a 'protected position'

| Degree of Enclosure | SURFACE TREATMENT TYPE       |         |         |
|---------------------|------------------------------|---------|---------|
|                     | Level of corrosion potential |         |         |
|                     | Level 1                      | Level 2 | Level 3 |
| Enclosed            | A                            | B       | C       |
| Unenclosed          | B                            | C       | D       |



Figure 2 Maximum extent of openings in masonry walls for steelwork to be deemed to be 'enclosed'

TABLE 3

TREATMENTS REQUIRED TO ACHIEVE REQUIRED SURFACE TREATMENT TYPE

| Surface Treatment Type | Black Steel  | Galvanised Steel  |
|------------------------|--|---|
| A                      | No protection required.  | No additional protection required.  |
| B                      | Remove loose scale by hand or power wire brushing. Paint with one coat of a rust inhibitive alkyd primer or equivalent.  | No additional protection required.  |
| C                      | Prepare surface by power wire brushing or abrasive grit blasting. Apply one coat of a rust inhibitive alkyd primer, followed by one finish coat of all-weather gloss acrylic paint.  | No additional protection required.  |
| D                      | Prepare surface by abrasive grit blasting or pickling (class 2 1/2) followed by one of the following: <ul style="list-style-type: none"> <li>• Apply one coat of an inorganic zinc silicate, followed by one coat of all-weather gloss acrylic with UV protector.</li> <li>• Hot dip galvanising.</li> <li>• Epoxy high corrosion-resistant system or equivalent.</li> </ul> | Apply primer coat followed by a finish coat, both of zinc dust or zinc oxide type. Both coats may either be brushed or sprayed. In the case of decking, the treatment should be applied to the underside before installation. |

\*Note: For lintels supporting masonry some building authorities may require a higher level of surface treatment.



## OTHER PUBLICATIONS

OneSteel produces a number of publications. Others related to residential construction include:



**DuraGal Flooring  
System® Brochure**



**DuraGal® Construction  
Manual**



**DuraGal® Verandah  
Beam Spanning Tables**

For more information on these publications contact OneSteel Direct toll free on 1800 1 STEEL (1800 1 78335) in Australia or visit our website at [www.onesteel.com](http://www.onesteel.com)



personalise your experience

## My Needs. My Solutions. MyOneSteel.

### STEEL ADVICE AROUND THE CLOCK

If you're looking for **advice on steel**, then at OneSteel's website you'll find everything from A to Z, covering the **largest range of steel products and services**, technical information, design aids, case studies, shareholder information, where your steel suppliers are, and much more, it's **your 24 Hour reference**.

### FULLY PERSONALISED FOR YOUR NEEDS

**MyOneSteel** is one of the latest enhancements to the OneSteel website. The new design allows for each user to register and then personalise a homepage to suit their interests. This allows **faster access to the information you want**, without the things you don't need by selecting your products, your news – **everything that matters to you and for your business**.

FREECALL 1800 178 335 WEBSITE [www.onesteel.com](http://www.onesteel.com) EMAIL [onesteeldirect@onesteel.com](mailto:onesteeldirect@onesteel.com)



**onesteel**  
market mills

[www.onesteel.com](http://www.onesteel.com)



**onesteel**  
market mills

## ONESTEEL DIRECT

Freecall 1800 178 335

Website [www.onesteel.com](http://www.onesteel.com)

Freefax 1800 101 141

Email [onesteeldirect@onesteel.com](mailto:onesteeldirect@onesteel.com)

Postal address

Locked Bag 8825

Wollongong DC

NSW 2500 Australia

DISTRIBUTED BY

This publication has been prepared by OneSteel Market Mills which OneSteel Manufacturing Pty Limited ABN 42 004 651 325 is a part. Please note that any specifications or technical data referred to in this publication are subject to change and/or variation or improvement without notice and no warranty as to their suitability for any use is made. Users of this publication - to ensure accuracy and adequacy for their purposes - are requested to check the information provided in this publication to satisfy themselves as to its appropriateness and not to rely on the information without first doing so. Unless required by law, the company cannot accept any responsibility for any loss, damage or consequence resulting from the use of this publication. This publication is not an offer to trade and shall not form any part of the trading terms in any transaction. © Copyright 2003-2006. Issue 6. Printed March 2006. BC0379. Registered Trademarks of OneSteel Manufacturing Pty Limited ABN 42 004 651 325: 300PLUS®.

9 320075 046118

